

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

5. Lease Designation and Serial No.

SF-079485-A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 30-4 Unit

8. Well Name and No.

San Juan 30-4 Unit #41

9. API Well No.

30-039-25937

10. Field and Pool, or exploratory Area

Blanco Mesa Verde/
Basin Dakota

11. County or Parish, State

Rio Arriba NM

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Taurus Exploration U.S.A., Inc.

3. Address and Telephone No.

2198 Bloomfield Highway; Farmington, NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1260' FSL, 1905' FWL, Sec. 18, T30N, R4W, N.M.P.M.

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Production Casing
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

10/5/98 Ran 26 joints 5 1/2", 17#, L-80 LTC casing (1042') and 175 joints 5 1/2", 17#, K-55, LT&C casing (7722') set at 8776'. DV tool set at 6897'. Cemented 1st stage with 260 sks 50/50 Class H poz with 2% gel, 5#/sk Gilsonite, 1/4# sk Flocele and 0.4% Halad-9 (364 cu. ft.). Plug down 4:30 am 10/5/98. Opened DV tool and circ. 2 hrs. Cemented 2nd stage with 280 sks 50/50 Class H poz with 2% gel, 5#/sk Gilsonite, 1/4# sk Flocele and 0.4% Halad-9 (392 cu. ft.). Ran GR-CBL log. Top of cement at 5468'.

14. I hereby certify that the foregoing is true and correct

Signed

Title Production Superintendent

Date 10/15/98

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States a false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side

WOOD

NOV 25 1998
FARMINGTON DISTRICT OFFICE
BY