

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other instructions on reverse side)

FORM APPROVED
OMB NO. 1004-0137
Expires: February 28, 1995

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other _____		7. UNIT AGREEMENT NAME San Juan 30-4 Unit	
b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR ☐ Other _____		8. FARM OR LEASE NAME, WELL NO. San Juan 30-4 Unit 41	
2. NAME OF OPERATOR Taurus Exploration U.S.A., Inc.		9. API WELL NO. 30-039-25937	
3. ADDRESS AND TELEPHONE NO. 2198 Bloomfield Highway; Farmington, NM 87401		10. FIELD AND POOL, OR WILDCAT Blanco MesaVerde	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface 1260' FSL, 1905' FWL At top prod. interval reported below At total depth		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 18, T30N, R4W, N.M.P.M.	
14. PERMIT NO.		DATE ISSUED	
12. COUNTY OR PARISH Rio Arriba		13. STATE NM	
15. DATE SPLUDD 8/25/98	16. DATE T.D. REACHED 10/3/98	17. DATE COMPL. (Ready to prod.) 11/13/98	18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 7408 GR
19. ELEV. CASINGHEAD 7408			
20. TOTAL DEPTH, MD & TVD 8876'	21. PLUG, BACK T.D., MD & TVD 8848'	22. IF MULTIPLE COMPL., HOW MANY* 2	23. INTERVALS DRILLED BY →
24. PRODUCING INTERVAL(S), OF THIS COMPLETION - TOP, BOTTOM, NAME (MD AND TVD)* 5481' - 6786' MesaVerde			25. WAS DIRECTIONAL SURVEY MADE Yes
26. TYPE ELECTRIC AND OTHER LOGS RUN Micro Log, Temp. Log, HRI Log, Den.-Neu. Log, GR-CRL-CBL			27. WAS WELL CORED No
28. CASING RECORD (Report all strings set in well)			
CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE
10 3/4"	40.5	321'	15
7 5/8"	26.40	4635'	9 7/8
5 1/2"	17	8776'	6 3/4
			256
29. LINER RECORD			
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*
30. TUBING RECORD			
SIZE	DEPTH SET (MD)	PACKER SET (MD)	
1 1/2"	6610'	6809'	
31. PERFORATION RECORD (Interval, size and number) Size 0.34: 6564, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 83, 6610, 17, 23, 24, 25, 26, 27, 28, 29, 30, 31, 76, 6700, 07, 09, 27, 65, 67, 80, 86 (35 Holes) 1JSPF cont'd next page			
32. ACID, SHOT, FRACTURE, CEMENT SOLLEEZE, ETC.			
DEPTH INTERVAL (MD)		AMOUNT AND KIND OF MATERIAL USED	
6564' - 6786'		72,800 Gallons, Slickwater,	
		90,000# 20/40 Sand.	
6031' - 6432'		62,200 Gallons, Slickwater,	
		80,000# 20/40 Sand.	
33.* PRODUCTION			
DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping - size and type of pump) Flowing	
WELL STATUS (Producing or shut-in) Shut-In			
DATE OF TEST 11/13/98	HOURS TESTED 7 Day Shut In	CHOKE SIZE	PROD'N. FOR TEST PERIOD →
FLOW. TUBING PRESS. SI-1110#	CASING PRESSURE SI-1110#	CALCULATED 24-HOUR RATE →	OIL - BBL.
GAS - MCF.		WATER - BBL.	
OIL GRAVITY - API (CORR.)			
34. DISPOSITION OF GAS (Sold, used for fuel, vented etc.) To Be Sold			
TEST WITNESSED BY Perry Kirk			
35. LIST OF ATTACHMENTS None			
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records			
SIGNED _____		TITLE Production Superintendent	

*(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof, cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	GEOLOGIC MARKERS		
				NAME	MEAS. DEPTH	TOP TRUE VERT. DEPTH
38.			31. 6031, 60, 70, 79, 81, 6110, 34, 70, 6207, 10, 33, 68 6312, 21, 26, 28, 46, 47, 49, 57, 59, 69, 71, 6405, 07, 12, 15, 17, 30, 32 (30 Holes) 1JSPF 5481, 82, 85, 98, 5525, 43, 49, 5602, 06, 09, 5613, 20, 26, 31, 87 (15 Holes) 1JSPF 32. 5481' - 5687' - 73,000 Gallons, 60 Q Foam, 150,000# 20/40 Sand.	Ojo Alamo	3475	
				Kirtland	3700	
				Fruitland	3945	
				Pictured Cliffs	4150	
				Lewis	4440	
				Cliff House	6010	
				Menefee	6338	
				Point Lookout	6560	
				Mancos	7100	
				Gallup	7670	
				Greenhorn	8577	
				Dakota	8754	