

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1804-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals.

**SUBMIT IN TRIPLICATE**

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Phillips Petroleum Company

3. Address and Telephone No.

5525 Highway 64, NBU 3004, Farmington, NM 87401 505-599-3454

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit A, 1045' FNL & 1081' FEL  
Section 23, T30N, R5W

5. Lease Designation and Serial No.

SF-078738

6. If Indian, Allottee or Tribe Name

7. Unit or CA, Agreement Designation

San Juan 30-5 Unit

8. Well Name and No.

San Juan 30-5 Unit #249

9. API Well No.

30-039-29320 25972

10. Field and Pool, or exploratory Area

Basin Fruitland Coal

11. County or Parish, State

Rio Arriba, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Spud Report  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9/20/98

MIRU Big A #37. Spud 12-1/4" hole @ 0630 hrs 9/21/98. Drilled ahead to 376'. RIH w/9-5/8" 36# K-55 casing and landed @ 371'. RU BJ to cement. Pumped 10 bbls mud flush and 10 bbls water spacer ahead. Pumped 185 sx (222 cf) C1 H cement, 1/4#/sx Cello-Flake, 2% CaCl2 mixed at 15.6 ppg w/1.20 yield. Rate 3 bpm at 100 psi, dropped wood plug & displaced with 26.4 bbls. Plug down @ 1827 hrs 9/21/98. Left 30' of cement in 9-5/8" casing and had 5 bbls (28 cf) returns to surface. WOC - 9.5 hrs. NU Bradenhead & BOP. PT to 200 psi 3 min and 1500 psi for 10 min. Good test.

14. I hereby certify that the foregoing is true and correct

Signed Patsy Clayton Title Regulatory Assistant Date 9-23-98

(This space for Federal or State office use)

Approved by \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_  
Conditions of approval, if any:

**ACCEPTED FOR RECORD**

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\* See Instruction on Reverse Side

**FARMINGTON DISTRICT OFFICE**

BY [Signature]

NMOC