Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED	
Budget Bureau No. 10	04-013
Expires: March 31.	1993

Expires, March 31, 1993

5. Lease Designation and Serial No. SF-078997 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT - " for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE I. Type of Well <u>San Juan 30-5 Unit</u> Oil X Gas 8. Well Name and No. 2. Name of Operator SJ 30-5 Unit #243 Phillips Petroleum Company 9. API Well No. 3. Address and Telephone No. 30-039-25984 5525 Highway 64, NBU 3004, Farmington, NM 87401 10. Field and Pool, or exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Unit G, 2232.5' FNL & 1657' FEL Basin Fruitland Coal Section 15, T30N, R5W 11. County or Parish, State Rio Arriba. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion **New Construction** X Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Spud Notice Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) 11/6/98 MIRU Big A #37. Spud 12-1/4" hole @ 0130 hrs 11/7/98. Drilled ahead to 380'. Circ. hole. RIH w/9-5/8" 36#. J-55 casing and set @ 374'. RU BJ to cement. Pumped 10 bbl mud flush and 10 bbl FW spacer. Pumped 185 sx (222 cf) Class H cement w/2% CaCl2 & 1/4#/sx of Cello-Flake, mixed at 15.6 ppg w/1.20 yield. Dropped wood plug & displaced w/27.2 bbls water. Rate 2 bpm at 100 to 125 psi. Plug down at 1636 hrs 11/7/98. Circulated 6 bbls cement to surface. WOC. NU Bradenhead and BOP. PT to 200 psi 3 min and 1500 psi for 10 min. Good test. (This space for Federal of State office use) Approved by Conditions of approval, if any: ACCEPTED FOR ALLOCKL Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any falses 11998 or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side

MAIOCE

FARMINGTON DISTRICT OFFICE