

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

## Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator

**BURLINGTON  
RESOURCES**

OIL & GAS COMPANY

5. Address & Phone No. of Operator

PC Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1850' FNL, 860' FEL, Sec. 24, T-30-N, R-7-W, NMPM

5. Lease Number

SF-079382

6. If Indian, All. or  
Tribe Name

7. Unit Agreement Name

San Juan 30-6 Unit

Well Name & Number

San Juan 30-6 U #76E

API Well No.

30-039-26004

10. Field and Pool

Basin Dakota

11. County and State

Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input checked="" type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

11-29-98 Drill to intermediate TD @ 3750'. Circ hole clean. TOOH. TIH, ran logs. TOOH. TIH, circ hole clean. TOOH.

11-30-98 TIH w/91 jts 7" 20# J-55 ST&C csg, set @ 3736'. Pump 20 bbl wtr ahead. Cmtd first stage w/175 sx Class "B" 50/50 poz w/2% gel, 2% calcium chloride, 10 pps Gilsonite, 0.5 pps Cellophane (247 cu.ft.). Circ 20 bbl cmt to surface. Stage tool set @ 2994'. Pump 20 bbl wtr ahead. Cmtd second stage w/320 sx Class "B" neat cmt w/3% sodium metasilicate, 10 pps Gilsonite, 0.5 pps Cellophane (931 cu.ft.). Circ 56 bbl cmt to surface. WOC. PT BOP & csg to 1500 psi/30 min, OK. Drilling ahead.

12-4-98 Drill to TD @ 8077'. Circ hole clean. TOOH. TIH w/189 jts 4 1/2" 10.5# J-55 ST&C csg, set @ 8071'. Pump 20 bbl wtr, 20 bbl chemical wash, 20 bbl wtr ahead. Cmtd w/545 sx Class "H" 50/50 poz w/2% gel, 0.4% fluid loss, 0.2% retardant, 5 pps Gilsonite, 0.25 pps Cellophane (692 cu.ft.). Displace w/128.6 bbl wtr. Circ 20 bbl wtr to surface. WOC. PT csg to 3800 psi/15 min, OK. ND BOP. NU WH. RD. Rig released.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 12/8/98  
no

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

CONDITION OF APPROVAL, if any:

**ACCEPTED FOR RECORD**

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

**MAR 12 1999**

**NMOC**

**FARMINGTON FIELD OFFICE**  
BY [Signature]