

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BLM

Sundry Notices and Reports on Wells

99 JUL 16 PM 2:21

1. Type of Well
GAS

070 FARMINGTON, NM

- 5. Lease Number
NM-4453
- 6. If Indian, All. or
Tribe Name
- 7. Unit Agreement Name

2. Name of Operator

**BURLINGTON
RESOURCES** OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 875-1700

4. Location of Well, Footage, Sec., T, R, M
1850' FSL, 1270' FEL, Sec.1, T-30-N, R-5-W, NMPM

NSL-4254

- 8. Well Name & Number
Carson SRC #2A
- 9. API Well No.
30-039-26018
- 10. Field and Pool
Blanco MV/Basin DK
- 11. County and State
Rio Arriba Co, NM

RECEIVED
JUL 23 1999
OIL CON. DIV.
DIST. 3

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input checked="" type="checkbox"/> Other -
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Conversion to Injection

13. Describe Proposed or Completed Operations

- 7-10-99 Drill to intermediate TD @ 3782'. Circ hole clean. TOOH. TIH w/90 jts 7" 20# J-55 ST&C csg, set @ 3774'. Pump 20 bbl wtr, 20 bbl chemical wash, 20 bbl wtr ahead. Cmtd w/435 sx Class "B" neat cmt w/3% sodium metasilicate, 0.25 pps Cellophane, 5 pps Kolite (1266 cu.ft.). Tailed w/90 sx Class "B" neat cmt w/2% sodium metasilicate, 2% calcium chloride, 0.25 pps Cellophane, 5 pps Kolite (155 cu.ft.). Circ 60 bbl cmt to surface. WOC.
- 7-11-99 PT BOP & csg to 1500 psi/30 min, OK. Drilling ahead.
- 7-13-99 Drill to TD @ 8210'. Circ hole clean. TOOH. TIH w/92 jts 4 1/2" 10.5# J-55 ST&C csg, 98 jts 4 1/2" 11.6# K-55 LT&C csg, set @ 8204'. Pump 10 bbl wtr, 20 bbl chemical wash, 10 bbl wtr ahead. Cmtd w/411 sx Class "B" 50/50 poz w/2% gel, 5 pps Kolite, 0.25 pps Flocele, 0.5% fluid loss, 0.2% defoamer (649 cu.ft.). Displace w/129 bbl wtr. WOC. PT csg to 3800 psi/15 min, OK. ND BOP. NU WH. RD. Rig released.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 7/16/99

(This space for Federal or State Office use)
APPROVED BY _____ Title _____ Date _____
CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD

JUL 21 1999

NMOCD

FARMINGTON FIELD OFFICE
BY [Signature]