

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

90 JUL 27 1999 12

070 FARMINGTON, NM

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 826-9700

4. Location of Well, Footage, Sec., T, R, M

880' FSL, 940' FEL, Sec. 25, T-30-N, R-7-W, NMPM

5. Lease Number
SF-079382

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

San Juan 30-6 Unit
8. Well Name & Number
San Juan 30-6 U #129
9. API Well No.
30-039-26124
10. Field and Pool
Basin Dakota
11. County and State
Rio Arriba Co, NM

RECEIVED
AUG 3 4 1999
OIL CON. DIV.
DIST. 3

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment

Type of Action

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☒ Altering Casing
☐ Other -
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut off
☐ Conversion to Injection

13. Describe Proposed or Completed Operations

7-17-99 Drill to 3450'. Circ hole clean. TOOH. TIH, ran logs. TOOH. TIH, drill to intermediate TD @ 3529'. Circ hole clean. TOOH.
7-18-99 TIH w/84 jts 7" 20# J-55 ST&C csg, set @ 3521'. Pump 20 bbl wtr ahead. Cmdt first stage w/195 sx Class "B" neat cmt w/2% sodium metasilicate, 2% calcium chloride, 0.5 pps Cellophane, 7 pps Kolite (335 cu.ft.). Displace w/41 bbl wtr & 100 bbl mud. Circ 16 bbl cmt to surface. WOC. Stage tool set @ 2766'. Pump 20 bbl wtr, 20 bbl chemical wash, 20 bbl wtr ahead. Cmdt second stage w/365 sx Class "B" neat cmt w/3% sodium metasilicate, 0.5 pps Cellophane, 7 pps Kolite (1062 cu.ft.). Displace w/112 bbl wtr. Circ 35 bbl cmt to surface. WOC. PT BOP & csg to 1500 psi/30 min, OK. Drilling ahead.
7-22-99 Drill to TD @ 7841'.
7-23-99 Circ hole clean. TOOH. TIH, ran logs. Circ hole clean.
7-24-99 Circ hole clean. TOOH. TIH w/97 jts 4 1/2" 10.5# J-55 ST&C csg, 84 jts 11.6# K-55 LT&C csg, set @ 7838'. Pump 10 bbl chemical wash, 10 bbl wtr ahead. Cmdt w/434 sx Class "B" 50/50 poz w/2% gel, 5 pps Kolite, 0.25 pps Flocele, 0.5 pps dispersant, 0.2% retardant (686 cu.ft.). Displace w/102.5 bbl wtr. No cmt circ to surface. WOC. PT csg to 3800 psi/15 min, OK. ND BOP. NU WH. RD. Rig released.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 7/26/99

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

JUL 20 1999

NMOCD

FARMINGTON FIELD OFFICE
BY [Signature]