

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT -" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

ENERGEN RESOURCES CORPORATION

3. Address and Telephone No.

2198 Bloomfield Highway, Farmington, NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

470' FNL, 1665' FEL, Sec. 30, T30N, R4W, N.M.P.M.

5. Lease Designation and Serial No.

SF-079488-A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Carson 5

9. API Well No.

30-039-26133

10. Field and Pool, or exploratory Area

Blanco MV

11. County or Parish, State

Rio Arriba NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Casing Report
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/24/99 Drilled to 4670'. Ran 105 jts., 7", 23# J-55 LT&C casing 4653' set at 4668'. DV tool at 3787'. Cement 1st stage with 225 sks class B, 1% CaCL2 10#/sk gilsonite and 1/2#/sk flocele (281 cu. ft.) Plug down 10:45pm 8/24/99. Open stage tool and circ. for 2 1/2 hrs. Cement 2nd stage with 560 sks 65/35 poz with 6% gel, 1/2#/sk flocele, 10#/sk gilsonite, and 2% CaCL2 followed by 100 sks class B, 10#/sk gilsonite, 1/2#/sk flocele and 1% CaCL2. (1211 cu. ft.) Plug down 4:45am 8/25/99. Circ. 32 BBL slurry to surface. WOC. Tested casing to 1200 psi - OK.

14. I hereby certify that the foregoing is true and correct

Signed

Title Production Superintendent

Date 9/3/99

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side

SEP 08 1999
FARMINGTON FIELD OFFICE
BY 220