

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or extend to a different reservoir.

Use "APPLICATION FOR PERMIT -" for such proposals

SUBMIT IN TRIPLICATE

070 FARMINGTON, NM

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

ENERGEN RESOURCES CORPORATION

3. Address and Telephone No.

2198 Bloomfield Highway, Farmington, NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

830' FNL, 820' FWL, Sec. 31, T30N, R4W, N.M.P.M.

5. Lease Designation and Serial No.

SF-079488

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation  
San Juan 30-4 Unit

8. Well Name and No.

San Juan 30-4 Unit 33A

9. API Well No.

30-039-26144

10. Field and Pool, or exploratory Area

Blanco MV/Basin DK

11. County or Parish, State

Rio Arriba NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Case  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

7/17/99 Drilled to 4592'. Ran 107 jts., 7 5/8, 26.4# J-55 casing 4578' set at 4592'. Stage collar at 3788'. Cemented 1st stage with 235 sks Class B, 10#/sk gilsonite, 1/2#/sk flocele and 2% CaCL2. (294 cu. ft.) Plug down 8 am 7/17/99. Open stage tool. Circ. 4 hrs. Cemented 2nd stage with 650 sks 65/35 poz, 6% gel, 10#/sk gilsonite, 1/2#/sk flocele 2% CaCL2 followed by 100 sks Class B with 10#/sk gilsonite, 1/2#/sk flocele 2% CaCL2. (1379 cu. ft.) Plug down 2:15 pm 7/17/99. Circ. 87 sks cement to surface. WOC. Tested casing to 2000 psi - OK.

RECEIVED  
JUL 26 1999  
OIL CON. DIV.  
DIST. 3

14. I hereby certify that the foregoing is true and correct

Signed

*Monica Taylor*

Title Production Assistant

Date 7/22/99

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\* See Instruction on Reverse Side

FARMINGTON FIELD OFFICE  
BY *SM*