

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

070 FARMINGTON, NM

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Phillips Petroleum Company

3. Address and Telephone No.

5525 Highway 64, NBU 3004, Farmington, NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit N, 860' FSL & 1375' FWL
Section 13, T30N, R5W

RECEIVED
JUN 14 1999
OIL CON. DIV.
DIST. 3

5. Lease Designation and Serial No.

SF-080538

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 30-5 Unit

8. Well Name and No.

SJ 30-5 Unit #111

9. API Well No.

30-039-26158

10. Field and Pool, or exploratory Area

Blanco Mesaverde and
Basin Dakota

11. County or Parish, State

Rio Arriba NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud Report
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6/7/99

MIRU Key Energy #49. Spud 12-1/4" hole @ 2345 hours 6/7/99. Drilled ahead to 368'. RIH w/9-5/8" 36# J-55 casing and set @ 364'. RU BJ to cement. Pumped 5 bbls FW, 10 bbls mud clean and 10 bbls FW, then pumped 195 sx (234 cf) Class H cement w/2% CaCl2 & 1/4#/sx Cello-flake @ 15.6 ppg with a yield of 1.20. Dropped wood plug and displaced with 27.5 bbls FW. Plug down 1140 hrs 6/8/99. Circulated 19 sx (23 cf) cement to surface. WOC.

NU WH & BOP. Pressure test blind rams, casing, and manifold to 200 psi for 3 minutes and 2000 psi for 10 minutes. Good test.

APD/ROW Process

14. I hereby certify that the foregoing is true and correct

Signed

Patsy Chaston

Title

Regulatory Assistant

Date

6/9/99

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

ACCEPTED FOR RECORD

JUN 10 1999

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See instruction on Reverse Side

FARMINGTON FIELD OFFICE
BY *[Signature]*

NMOCD