

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT -" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
ENERGEN RESOURCES CORPORATION

3. Address and Telephone No.
2198 Bloomfield Highway, Farmington, NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
1189' FSL, 1133' FEL, Sec. 19, T30N, R4W, N.M.P.M.
P

5. Lease Designation and Serial No.

SF-07948-A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation
San Juan 30-4 Unit

8. Well Name and No.
San Juan 30-4 Unit 42A

9. API Well No.
30-039-26190

10. Field and Pool, or exploratory Area
E. Blanco PC/ Blanco MV

11. County or Parish, State
Rio Arriba NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☒ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6/13/00 Ran 112 jts 7" 20 & 23# J-55 casing 4658' set at 4670'. Stage collar at 3900'. Cemented 1st stage with 210 sx 50/50 poz, 2% gel, 10#/sk gilsonite, 1/4#/sk flocele and 1% CaCl2 (279 cu. ft.) Plug down at 1:45 pm 6/12/00. Circ hole 3 hrs. Cemented 2nd stage with 600 sx 65/35 poz, 6% gel, 10#/sk gilsonite, 1/4#/sk flocele and 2% CaCl2 followed by 100 sx Class B, 10#/sk gilsonite, 1/4#/sk flocele, and 2% CaCl2 (1303 cu. ft.) Lost returns 40 BBLs into displacement. Plug down 5 pm 6/12/00. WOC. Ran temp survey-TOC 1700'. WOC. Tested casing to 1200 psi - OK.

14. I hereby certify that the foregoing is true and correct

Signed

Monica Papp

Title Production Assistant

ACCEPTED FOR RECORD
Date 6/22/00

(This space for Federal or State office use)

Approved by

Title

Date

SEP 14 2000

Conditions of approval, if any:

FARMINGTON FIELD OFFICE
BY

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side