

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals 300 SEP 22 PM 12:03

SUBMIT IN TRIPLICATE

070 FARMINGTON

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
ENERGEN RESOURCES CORPORATION

3. Address and Telephone No.
2198 Bloomfield Highway, Farmington, NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
2395' FNL, 2510' FEL, Sec. 22, T30N, R4W, N.M.P.M.

5. Lease Designation and Serial No.
SF-079487

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation
San Juan 30-4 Unit

8. Well Name and No.
San Juan 30-4 Unit 47

9. API Well No.
30-039-26316

10. Field and Pool, or exploratory Area
East Blanco Pictured Cliffs

11. County or Parish, State
Rio Arriba NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
- ☒ Subsequent Report
- ☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
- ☐ Recompletion
- ☐ Plugging Back
- ☐ Casing Repair
- ☐ Altering Casing
- ☐ Other

- ☐ Change of Plans
- ☐ New Construction
- ☐ Non-Routine Fracturing
- ☒ Water Shut-Off
- ☐ Conversion to Injection
- ☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

TD @ 4750'. Ran 105 jts 4-1/2" 10.5# J-55 ST&C casing, set @ 4742', stage tool @ 3701'. RU Halliburton & cement 1st stage w/300 sks 50/50 Poz "H", 2% gel, .3% Halad-344, 10#/sk gilsonite, 1/4#/sk flocele, 2% CaCl2(438 cu. ft.). Plug down @ 7:00 AM 9/20/00. Dropped bomb & opened stage tool, circ 15 sks cement to surface. Cement 2nd stage w/600 sks 65/35 Poz "H", 6% gel, 10#/sk gilsonite, 1/4#/sk flocele, 2% CaCl2(750 cu. ft.). Tailed w/100 sks Class "H", 2% CaCl2, 10#/sk gilsonite, 1/4#/sk flocele(125 cu. ft.). Plug down @ 10:00 AM 9/20/00. Circ. 55 sks cement to surface. WOC. RD Halliburton. ND BOP. Rig released @ 4:00 PM 9/20/00.

14. I hereby certify that the foregoing is true and correct

Signed *[Signature]*

Title Drilling & Completion Foreman

ACCEPTED FOR RECORD

(This space for Federal or State office use)

Approved by

Title

Date OCT 26 2000

Conditions of approval, if any:

FARMINGTON FIELD OFFICE
BY *[Signature]*

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.