Form 3160-5

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED
Budget Buread No. 1004-0135
Expires: March 31 1993

stage w/260 sks 5 @ 4:00 PM 8/11/00	ft). Plug down @ 7:4 g to 1200# - OK. regoing is true and correct Change State office use)	, 10#/sk gilsonite, 1% CaCl2, 1/4#/sk floor/480 sks 65/35 Poz "B", 6% gel, 10#/sk gils 5 PM 8/11/00. Circ 100 sks cement to surface and the su	lsonite, 1/4#/sk flocele,
stage w/260 sks 5 @ 4:00 PM 8/11/00 2% CaCl2 (941 cu BOP & test casing). Cement 2nd stage w ft). Plug down @ 7:4 g to 1200# - OK.	7/480 sks 65/35 Poz "B", 6% gel, 10#/sk gi 5 PM 8/11/00. Circ 100 sks cement to surfa	Isonite, 1/4#/sk flocele, ace.RD Halliburton. WOC. NU
stage w/260 sks 5 @ 4:00 PM 8/11/00 2% CaCl2 (941 cu). Cement 2nd stage w ft). Plug down @ 7:4	/480 sks 65/35 Poz "B", 6% gel, 10#/sk gi	lsonite, 1/4#/sk flocele,
stage w/260 sks 5 @ 4:00 PM 8/11/00 2% CaCl2 (941 cu). Cement 2nd stage w ft). Plug down @ 7:4	/480 sks 65/35 Poz "B", 6% gel, 10#/sk gi	lsonite, 1/4#/sk flocele,
stage w/260 sks 5 @ 4:00 PM 8/11/00 2% CaCl2 (941 cu). Cement 2nd stage w ft). Plug down @ 7:4	/480 sks 65/35 Poz "B", 6% gel, 10#/sk gi	lsonite, 1/4#/sk flocele,
stage w/260 sks 5 @ 4:00 PM 8/11/00 2% CaCl2 (941 cu). Cement 2nd stage w ft). Plug down @ 7:4	/480 sks 65/35 Poz "B", 6% gel, 10#/sk gi	lsonite, 1/4#/sk flocele,
stage w/260 sks 5 @ 4:00 PM 8/11/00 2% CaCl2 (941 cu). Cement 2nd stage w ft). Plug down @ 7:4	/480 sks 65/35 Poz "B", 6% gel, 10#/sk gi	lsonite, 1/4#/sk flocele,
stage w/260 sks 5 @ 4:00 PM 8/11/00 2% CaCl2 (941 cu). Cement 2nd stage w ft). Plug down @ 7:4	/480 sks 65/35 Poz "B", 6% gel, 10#/sk gi	lsonite, 1/4#/sk flocele,
stage w/260 sks 5 @ 4:00 PM 8/11/00 2% CaCl2 (941 cu). Cement 2nd stage w ft). Plug down @ 7:4	/480 sks 65/35 Poz "B", 6% gel, 10#/sk gi	lsonite, 1/4#/sk flocele,
stage w/260 sks 5 @ 4:00 PM 8/11/00 2% CaCl2 (941 cu). Cement 2nd stage w ft). Plug down @ 7:4	/480 sks 65/35 Poz "B", 6% gel, 10#/sk gi	lsonite, 1/4#/sk flocele,
stage w/260 sks 5 @ 4:00 PM 8/11/00 2% CaCl2 (941 cu). Cement 2nd stage w ft). Plug down @ 7:4	/480 sks 65/35 Poz "B", 6% gel, 10#/sk gi	lsonite, 1/4#/sk flocele,
0/11/00 5 117 :		sing, set @ 4890', stage tool @ 3866'. RU	Halliburton & cement 1st
escribe Proposed or Complete give subsurface location	ed Operations (Clearly state all pe ions and measured and true vertical	rtinent details, and give pertinent dates, including estimated date of start depths for all markers and zones pertinent to this work.)*	ing any proposed work. If well is directionally
		L_J Other	(Note: Report results of multiple completion on Completion or Recompletion Report and Log for
Final Aban	ndonment Notice	Altering Casing	Conversion to Injection
		Plugging Back Casing Repair	Non-Routine Fracturing Water Shut-Off
X Subsequent	ut Report	Recompletion	New Construction
Notice of I	Intent	Abandonment	Change of Plans
TYPE OF SUB	BMISSION	TYPE OF ACTION	
CHECK AP	PROPRIATE BOX(s)	TO INDICATE NATURE OF NOTICE, REPORT	, OR OTHER DATA
			11. County or Parish, State Rio Arriba NM
2410' FNL, 1615' FEL, Sec. 20, T30N, R4W, N.M.P.M.			
3. Address and Telephone No. 2198 Bloomfield Highway; Farmington, NM 87401 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			10. Field and Pool, or exploratory Area East Blanco PC/Blanco MV
			9. API Well No. 30-039-26330
Name of Operator ENERGEN RESOURCES			San Juan 30-4 Unit 45
Type of Wall Oil Well Gas Well	Other		8. Well Name and No.
SUBMIT IN TRIPLICATE			7. If Unit or CA, Agreement Designation San Juan 30-4 Unit
	•	FRMIT - " for such proposals	
Oo not use this form	for proposals to drill or	to deepen or reentry to a different reservoir.	6. If Indian, Allottee or Tribe Name
Do not use this form	SUNDRY NOTICES AND for proposals to drill or	to deepen or reentry to a different reservoir.	Lease Designation and Serial No. SF - 079487 - A If Indian, Allottee or Tribe Name

or representations as to any matter within its jurisdiction.