Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

5. Lease Serial No.

~-		

l	
CE	078740
\ - -	11/8/AII

SUNDRY	NOTICES	CINA	REPORT	S ON	WELLS
- 4				4	

Do not use this form for proposals to drill or to re-enter abandoned well. Use Form 3160-3 (APD) for such proposals: 6. If Indian, Allottee or Tribe Name

abandoned wen. User on		CA COA	V. DO.	V	
SUBMIT IN TRIPLICATE -	Other Instructions on re	(A)	3	7. If Unit or CA/A	greement, Name and/or No.
1. Type of Well Oil Well X Gas Well Other				San Juan 30-5 Unit 8. Well Name and No.	
2. Name of Operator Phillips Petroleum Company			-	S.J 30-5 Unit. 9. API Well No.	#48M
3a. Address 5525 Highway 64, NBU 3004, Farmingt	ľ	. Phone No. (include as 505-599-3454	rea code)	30-039-26367 10. Field and Pool	, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Surve Unit I, 1780' FSL & 1185' FEL	y Description)			Blanco Mesave Basin Dakota 11. County or Pari	
Section 20, T30N, R5W			,	Rio Arriba.	NM NM
12. CHECK APPROPRIA	ATE BOX(ES) TO INDIC	CATE NATURE OF NO	TICE, REPORT,	OR OTHER DATA	·
TYPE OF SUBMISSION		TYF	PE OF ACTION		
Notice of Intent	Acidize Alter Casing	Deepen Fracture Treat	Production Reclamatic	n (Start/Resume)	Water Shut-Off Well Integrity
X Subsequent Report	Casing Repair	New Construction	Recomplet	te X	Other
Final Abandonment Notice	Change Plans Convert to Injection	Plug and Abandon Plug Back	Temporari Water Dis	ily Abandon 7	" casing report
RIH w/8-3/4" bit & tagged cement Circulated hole. COOH. RIH w/7" mud clean, 10 bbls of FW w/red dy w/5#/sx Gilsonite, 1/4#/sx Cellomixed at 12.0 ppg w/2.37 yield. FCello-flake, 1% CaCl2, mixed at 1 down @ 13.55 hr w/1550#, good circasing. NU BOP & ran temperature 800' to 3715'. Test 7" casing, restrictions.	@ 295'. Drilled 20#, J-55 and set ve. Pumped Lead -flake, 6% gel, 10 pumped tail-50 sx 4.5 ppg w/1.40 yiec. No red dye og survey from surf	cement from 295' @ 3777'. RU to 455 sx (1078 cf #/sx CSE, 3% KCL (69.6 cf or 12.4 eld. Dropped pl r cement to surface to 3715'.	to 338'. D cement. Pu for 191 bbl ., 0.4% FL-5 6 bbls slur lug and disp face. WOC. S	orilled ahead umped 20 bbls s slurry) Type 3 ceplaced w/151 bet 7" slips ant @ 400' w/go	to 3780'. FW & 10 bbls be 3 35/65 POZ Static Free, ement w/1/4#/sx bbls FW. Plug and cut off bod cement @
14. I hereby certify that the foregoing is true and correct Name (Printed Typed) Author Auth	Patsy Clugston		/30/00	ulatory/Prorat	tion Clerk
	S SPACE FOR FEDE	Titls	TICE USE	Datel	JL 0 6 2000
Approved by Conditions of approval, if any, are attached. Approval	of this notice does not warr				
certify that the applicant holds legal or equitable title to	these rights in the subjec	lease		FARMIN	GION HELD OFFICE

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.