Submit 3 Copies To Appropriate District	State of New			Form C-103
Office District I	Energy, Minerals and N	latural Resources	CIVIDA Y VIDANO	Revised March 25, 1999
1625 N. French Dr., Hobbs, NM 87240			WELL API NO. 30-039-2	6464
District II 811 South First, Artesia, NM 87210	OIL CONSERVAT	ZA 10 13 10 11 10 -	5. Indicate Type of I	
District III 1000 Rio Brazos Rd., Aztec, NM 87410	2040 South I Santa Fe, NN		STATE X	FEE 🗆
District IV	Santa re, ini	AUG 2001	State Oil & Gas L	
2040 South Pacheco, Santa Fe, NM 87505	(O RECEIVE	E-347-46	case 110.
SUNDRY NOTICES AND REPORTS ON WELLS Log Lease Name or Unit Agreement Name: (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM CO1) FOR SUCH PROPOSALS.)				
1. Type of Well: Oil Well Gas Well X	Other	CS THE BEST	San Juan 31-6 Uni	it ~
2. Name of Operator	· · · · · · · · · · · · · · · · · · ·		8. Well No.	
Phillips Petroleum Company		017654	SJ 31-6 Unit #	
3. Address of Operator	Fauntan NM 07401		9. Pool name or Wil	
5525 Highway 64, NBU 3004, Farmington, NM 87401 Basin DK - 71599; Blanco MV-72319 4. Well Location				
Unit Letter:	1762' feet from the	South line and	660' feet from	the West line
Section 2	Township 30N	Range 6W	NMPM	County Rio Arriba
	10. Elevation (Show whet		c.)	
6280' GL 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data				
NOTICE OF INT		_	SEQUENT REP	
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	Ц	ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILL	ING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	MULTIPLE COMPLETION	CASING TEST AND CEMENT JOB		
OTHER:		OTHER:	Spud Report	
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.				
8/9/01 MIRU Key Energy #48M. Spud 12-1/4" bit hole @ 2245 hrs 8/9/01. Circ. hole. RIH w/9-5/8", 32.3# H-40 casing and landed @ 348'. RIH w/200 sx (282 cf - 50.22 bbl slurry) Type 3, 1/4#/sx Cello-flake, 2% CaCl2. Displaced with 25 bbls H2O. Plug down @ 0643 hrs 8/10/01. Circulated 15 bbls cement surface. WOC. NU WH & NU BOP. PT rams, manifold and casing to 200 psi and then 1500 psi - good test.				
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE Falsy	Mugston.	TITLE Sr. Regulatory	/Proration Clerk D	ATE 8/14/01
0	Patsy Clugston		Telephor	ne No. 505-599-3454
(This space for State CHAL SIGNS		In Fillians 24		AUG 1 7 2001
APPROVED BY	D BY CHAPILLE T. PERMIN	TITLE		ATE
Conditions of approval, if any:				