

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
OMB NO. 1004-0136
Expires: November 30, 2000



APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of Work <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. SF-080066	
1b. Type of Well <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zones		6. If Indian, Allottee or Tribe Name	
2. Name of Operator Phillips Petroleum Company		7. Unit or CA Agreement Name and No. San Juan 30-5 Unit	
3a. Address 5525 Highway 64, NBU 3004, Farmington, NM 87401		8. Lease Name and Well No. SJ 30-5 Unit #214	
3b. Phone No. (include area code) 505-599-3454		9. API Well No. 30-039-26512	
4. Location of Well (Report location clearly and in accordance with any State requirements)* At surface Unit N, 663' FSL & 1842' FWL At proposed prod. zone Same as above		10. Field and Pool, or Exploratory Basin Fruitland Coal	
14. Distance in miles and direction from nearest town or post office* 26 miles E/NE of Blanco, NM		11. Sec., T., R., M., or Blk. and Survey or Area N Section 5, T30N, R5W	
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drg. unit line, if any) 663'		12. County or Parish Rio Arriba,	
16. No. of Acres in lease 1158.12 acres		13. State NM	
17. Spacing Unit dedicated to this well 319.31 W/2			
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft.		20. BLM/BIA Bond No. on file ES00048	
19. Proposed Depth 3214'			
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 6444' Unprepared GL		22. Approximate date work will start* 4th Qtr 2000	
		23. Estimated duration 1 month	

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, shall be attached to this form:

- | | |
|---|--|
| 1. Well plat certified by a registered surveyor. | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan | 5. Operator certification. |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be required by the authorized officer. |

25. Signature 	Name (Printed/Typed) Patsy Clugston	Date 8/29/00
Title Sr. Regulatory/Proration Clerk		
Approved by (Signature) 	Name (Printed/Typed)	Date 9-23-00
Title Office		

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*(Instructions on Reverse)

This record is subject to technical and
procedural review pursuant to 43 CFR 3165.3
and appeal pursuant to 43 CFR 3165.4.DRILLING OPERATIONS AUTHORIZED ARE
SUBJECT TO COMPLIANCE WITH ATTACHED
"GENERAL REQUIREMENTS"

District I
190 Box 1980, Hobbs, NM 88241-1980
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

Form C-10
Revised October 18, 199
Instructions on back
Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

1 Well Number 30039-26512		2 Pool Code 71629		3 Pool Name Basin Fruitland Coal		
4 Property Code 009258		5 Property Name SAN JUAN 30-5 UNIT			6 Well Number 214	
7 OGRID No. 017654		8 Operator Name PHILLIPS PETROLEUM COMPANY			9 Elevation 6444'	

10 Surface Location


UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
N	5	30N	5W		663'	SOUTH	1842'	WEST	RIO ARriba

11 Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
N									

12 Dedicated Acres 319.31 W/2	13 Joint or Infill Y	14 Consolidation Code U	15 Order No.
----------------------------------	-------------------------	----------------------------	--------------

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR
NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



17 OPERATOR CERTIFICATION
I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief


Patsy Clugston
Signature
Patsy Clugston
Printed Name
Sr. Regulatory/Proration Clerk
Title
August 25, 2000
Date

18 SURVEYOR CERTIFICATION
I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

06/06/00
Date of Survey
Signature and Seal of Professional Surveyor:

Henry P. Broadhurst, Jr.
Certified Surveyor
NEW MEXICO
PROFESSIONAL SURVEYOR
11393

RIO ARriba COUNTY, NEW MEXICO
GROUND LEVEL ELEVATION: 6444'



PHILLIPS PETROLEUM COMPANY

WELL NAME: San Juan 30-5 Unit #214

DRILLING PROGNOSIS

1. Location of Proposed Well: Unit N, 663' FSL & 1842' FWL
Section 5, T30N, R5W
2. Unprepared Ground Elevation: @ 6444'
3. The geological name of the surface formation is San Jose.
4. Type of drilling tools will be rotary.
5. Proposed drilling depth is 3214'.
6. The estimated tops of important geologic markers are as follows:

<u>Nacimiento - 1454'</u>	
<u>Ojo Alamo - 2484'</u>	<u>Base of Coal - 3214'</u>
<u>Kirtland - 2689'</u>	<u>Picture Cliffs - 3219'</u>
<u>Fruitland - 2989'</u>	<u>Intern. Casing - 3084'</u>
<u>Top of Coal - 3104'</u>	<u>T. D. - 3214'</u>
7. The estimated depths at which anticipated water, oil, gas or other mineral bearing formations are expected to be encountered are as follows:

Water:	<u>Ojo Alamo - 2484' - 2689'</u>
Oil:	<u>none</u>
Gas & Water:	<u>Fruitland - 3104' - 3214'</u>
8. The proposed casing program is as follows:

Surface String: 9-5/8", 36#, J/K-55 @ 200' *

Intermediate String: 7", 20#, J/K-55 @ 3084'

Production Liner: 5-1/2", 3007' - TD (see details below)

* The surface casing will be set at a minimum of 200', but could be set deeper if required to maintain hole stability.
9. Cement Program:

Surface String = 102.5 sx Type III. Cement to surface w/110% excess of casing/hole annulus volume w/Type III cement + 2% bwoc Calcium Chloride + 0.25#/sx Cello-flake + 60.6% Fresh water (14.5 ppg/1.41 cf/sx yield). 24 hr compressive strength 2750 psi. 144.5 cf)

Intermediate String: **Lead Cement:** 349.4 sx Type III cement. Cement to surface - 110% excess casing/hole annular volume w/ Type III cement + 0.25#/sx Cello-flake + 5#/sx Gilsonite + 6% bwoc Bentonite + 10#/sx CSE + 3% bwow KCL + 0.4% bwoc FL-25 mixed + 0.02#/sx static free mixed at 12.0 ppg. (2.52 cf/sx yield = 880.48 cf)

Tail: 50 sx.(+/-) Type III cement w/1/4#/sx Cello-flake & 2% bwoc Calcium Chloride (14.5 ppg w/yield of 1.41 cf/sx) (70.5 cf)

Centralizer Program:

Surface: Total four (4) - 1 - 10' above shoe, top of 2nd, 4th, & 6th jts.

Intermediate: Total seven (7) - 10' above shoe, top of 1st, 2nd, 4th, 6th, 8th, & 1st jt. into shoe.

Turbulators: Total Three (3) - one at 1 jt below Ojo Alamo; 2 & 3 next 2 jts up.

Liner :

- If the coal is cleated a 5 1/2" 15.5# liner will be run in the open hole without being cemented.
- If the coal is not cleated, a 4-1/2" 11.6# liner will be run & cemented. The well will then be completed by fracture stimulation.

10. The minimum specifications for pressure control equipment which are to be used, a schematic diagram thereof showing sizes, pressure ratings (or) API series and the testing procedure and testing frequency are enclosed within the APD packet.
11. Drilling Mud Prognosis: Surface - spud mud on surface casing.
Intermediate - fresh water w/polymer sweeps. Bentonite as required for viscosity.
Below Intermediate - air drilled.
12. The testing, logging, and coring programs are as follows:
D.S.T.s or cores: _____
Logs: Mud logs only
13. Anticipated no abnormal pressures or temperatures to be encountered or any other potential hazards such as Hydrogen Sulfide Gas. Low risk H₂S equipment will be used.

Estimated Bottomhole pressures: Fruitland - +/- 1450 psi

BOP AND RELATED EQUIPMENT CHECK LIST

2M SYSTEM:

2 hydr. rams (pipe & blind) or hydr. ram and annular with blind ram on bottom

Kill Line (2-inch minimum)

1 kill line valve (2-inch minimum)

1 choke line valve

2 chokes (refer to diagram in attachment 1) on choke manifold

Upper kelly cock valve in open position with handle available

Safety valve (in open position) and subs to fit all drill strings in use (with handle available)

Pressure gauged on choke manifold

2 inch minimum choke line

Fill-up line above the uppermost preventer

The BOPs will be pressure tested according to Onshore Order #2 III, A 1 and 30% safety factor.