Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 200

C 111

5. Lease Serial No.

1	NMS	Fſ	١7	19.	Δ۶	≀ 6

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals

6. If Indian, Allottee or Tribe Name

apandoned well. Ose i on	11 3 100-3 (A1 D) 10	ama nu at	<u> تو د ده دن </u>	•
SUBMIT IN TRIPLICATE -	l l	7. If Unit or CA/Agreement, Name and/or No San Juan 30-4 Unit		
Type of Well Oil Well X Gas Well Other		A 123		II Name and No. Juan 30-4 Unit 51
2. Name of Operator Energen Resources Corporation 3a. Address 2198 Bloomfield Highway, Farmington 4. Location of Well (Footage, Sec., T., R., M., or Survey I 1310' FSL, 1745' FEL, Sec. 27, T30 12. CHECK APPROPRIATE TYPE OF SUBMISSION Notice of Intent X Subsequent Report	Description) N, RO4W, N.M.P.	3b. Plone No. (iAttacle error pode 505 - 325 - 6800) M. DICATE NATURE OF NOTICE TYPE OF Deepen Practure Treat New Construction Plug and Abandon	9. API 30-03 10. F East 11. C Rio	Well No. 39-26654 ield and Pool, or Exploratory Area Blanco Pictured Cliffs County or Parish, State Arriba NM DR OTHER DATA esume) Water Shut-Off Well Integrity Other
Final Abandonment Notice	Convert to Inject		Water Disposal	
tool. Attempt to circulate 06/22/02 TIH and close DV tool. 3500 psi - OK. TOH. 06/24/02 RU wireline. Ran GR C 06/25/02 TOH and lay down works 06/28/02 RU wireline. Perforat 07/01/02 Frac with 133,900 gals 07/09/02 MIRU. TIH with 2-3/8' 07/10/02 Clean out to PBTD. TO 4 squeeze holes @ 3950'. 07/11/02 NU cementing head. So followed by 100 sks Class B. 07/12/02 TIH w/bit. Tag cement	rformed or provide the If the operation results Notices shall be filed oction.) ' tubing and latthrough DV too. Drill out san CBL. TOC @ 3984 string. The well 4302' to sof 700 foam and tubing and clook. RU wireling and clook.	Bond No. on file with BLM/BIA. in a multiple completion or recomplements and requirements, including the control of the contro	reclamation, have reclamation, have reclamation, have TOH. 4743'. Tester to PBTD. Flow well to set casing to 3#/sk gilson WOC.	ent reports shall be filed within 30 day erval, a Form 3160-4 shall be filed once been completed, and the operator has circulate across DV st casing to back. To 1000 psi. Perf. Thorite, 2% CaCl2,
14. I hereby certify that the foregoing is true and correct Name (Printed Typed) Vicki Donaghey		Title Production	Assistant	
Vicki Draghay	C SPACE FOR FF	Date 07/25/02 DERAL OR STATE OFFICE	IISE	ACCEPTED FOR RECORD
	3 SPAUE FUR FE	Title	USE	
Approved by Conditions of approval, if any, are attached. Approval	of this notice does not			AUG n 2 2002
certify that the applicant holds legal or equitable title to which would entitle the applicant to conduct operations to	o those rights in the su	bject lease		FARMINGTON FIELD OFFICE

(Continued from page 1 of sundry)

- 07/15/02 NU cementing head. Squeeze with 150 sks 65/35 poz, 6% gel, 3#/sk gilsonite, 2% CaCl2 followed by 100 sks Class B, 2% CaCl2. (411 cu.ft.) WOC.
- 07/16/02 TIH w/bit. Tag cement @ 3594'. Drill out cement. Test casing to 500 psi. TOH. RU wireline. Ran CBL. TOC @ 3570'. Perf. 4 squeeze holes @ 3200'.
- 07/17/02 RU cementing head. Squeeze with 150 sks 65/35 poz, 6% gel, 3#/sk gilsonite, 2% CaCl2 followed by 100 sks Class B, 2% CaCl2. (411 cu.ft.). WOC.
- 07/18/02 TIH w/bit. Tag @ 3158'. Drill out cement.
- 07/19/02 Test casing to 1000 psi. RU wireline. Ran CBL. TOC @ 2600'. Verbal approval received from Wayne Townsend/BLM to suspend squeeze operations.
- 07/20/02 TIH. Drill CIBP @ 4050' and clean out to PBTD. TOH.
- 07/22/02 Ran 146 jts. 2-3/8" 7# tubing, set @ 4544'. Install wellhead. Release rig.