Form (A)	n 9- 8 pril 19	331 b 52)	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Agency Kindow Rock	Ļ
(Navajo), Arisona	
Allottee	

SLINDRY	NOTICES AN	D REPORTS ON WELLS	
SONDKI	NOTICES AN	D REPORTS ON WELLS	
OTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
OTICE OF INTENTION TO CHANGE		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.	
OTICE OF INTENTION TO TEST WA		SUBSEQUENT REPORT OF ALTERING CASING	
OTICE OF INTENTION TO REDRILL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.	
OTICE OF INTENTION TO SHOOT O		SUBSEQUENT REPORT OF ABANDONMENT	K
OTICE OF INTENTION TO PULL OR		SUPPLEMENTARY WELL HISTORY	V 254 97
OTICE OF INTENTION TO ABANDO	N WELL	- I can	
(INDICA	ATE ABOVE BY CHECK MARK NAT		58
		May 19. U. S. GEOLOGICAL	SU?
1 Magnolia-N	avajo	YEARING OF THE	
:ll N is lo	ocated _330_ft. from	line and 330 ft. from line of sec. 32	
y 34 32	20 W 14 W	*** The state of t	
(14 Sec. and Sec. No.)	(Twp.) (E	Range) (Meridian)	
lldoat	San Juan (County or 8	New Mexico	
ie elevation of the derric	k floor above sea level DETAILS	is 5197 ft.	
	DETAILS		ment-
In accessoring and expected depths In accessoring acc	DETAILS to objective sands; show sizes, y ing points, and all other rdance with ins at farmington, 1730 feet with th 60 sacks, as pipe at 70 fee at the surface n is ready for	structions from the USGS cement plugs were set from 1 60 sacks, from 900 to 1050 and from surface to bottom of 1. Required pipe marker and the location levelled. MAY 22 1956 OIL CON. C. ON.	ment-
In according to the names of and expected depths In according to the office of the feet with surface was set the control of the feet with the feet was set the	DETAILS to objective sands; show sizes, y ing points, and all other rdance with ins at farmington, 1730 feet with th 60 sacks, as pipe at 70 fee at the surface at the surface h is ready for	structions from the USGS cement plugs were set from 160 sacks, from 900 to 1050 ld from surface to bottom of it. Required pipe marker and the location levelled inspection.	ment-
In accordance of and expected depths In accordance of fice at 1600 to feet with surface was set Location and that this plan of wormpany western Dri 7114 Centre	DETAILS to objective sands; show sizes, y ing points, and all other rdance with ins at farmington, 1730 feet with th 60 sacks, as pipe at 70 fee at the surface at the surface h is ready for	weights, and lengths of proposed casings; indicate mudding jobs, cere important proposed work) structions from the USOS cement plugs were set from 1 60 sacks, from 900 to 1050 1 10 from surface to bottom of 1 11 Required pipe marker 1 and the location levelled 1 inspection. MAY 22 1950 OIL COM. COM.	ment-

C.

.

. (.