Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM - 0468128

6. If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS.

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals

7. If Unit or CA. Agreement Designation


(Note: Report results of multiple completion on Well

SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
	Corp. % NMOCO A Erec, NM 87410 334-6178 Description) F. 29 N., Kil3 W.	8. Well Name and No. 21 Central Totah 9. API Well No. 30045 07612 10. Field and Pool, or Exploratory Area Totah Callup 11. County or Parish, State San Juan, NM
2. CHECK APPROPRIATE BOX	(s) TO INDICATE NATURE OF NOTICE, REP	ORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTIO	DN
☐ Notice of Intent ☐ Subsequent Report ☐ Final Abandonment Notice	Abandonment Recompletion Plugging Back Casing Repair Altering Casing Other	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water

Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

See attached report for PLA



14. I hereby certify that the foregoing is true and correct		
Signed NMOCU Contract	Title	Date 5/21/98
(This space for Federal or State office use)		MAY 2 1 1000
Approved by Specific	Title	Date MAY 2 1 1998

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

TRIPLE P WELL SERVICE, INC.

CENTRAL TOTAH #21 RIG 6

START 4/3/98

END 4/8/98

- 1. Pull and laydown 123 rods (3075')
- Tubing parted laydown 105 joints (3300')
 Run in hole with overshot to 3250', no recovery
- 4. Perforate @ 3100'
- 5. Spot and balance plug @ 2066', 140sx, 165cf
- 6. Tag cement @ 1669'
- 7. Displace and balance, plug 1600' to 1100', 40sx, 47cf
- 8. Perforate @ 442', circulate cement to surface. 120sx, 142cf