
Form 9-381 a (Feb 1951)



(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUBSCUENT REPORT OF WATER SHUT-OFF. SUBSCUENT REPORT OF WATER SHUT-OFF. SUBSCUENT REPORT OF SHOOTING OR ACIDIZE. SUBSCUENT REPORT OF ACTERING ACASING. SUBSCUENT REPORT OF ACTERING ACASING. SUBSCUENT REPORT OF ACTERING ACASING. SUBSCUENT REPORT OF ACADINAC ACASING. SUBSCUENT REPORT OF		SUNDRY NOTICES AN	ND REPORTS ON WELLS
SUBSCOURT REPORT OF SHOOTING OR ACIDIZES OI CE OF INTENTION TO CREATE WATER SHUL-OFT OI CE OF INTENTION TO SHOOT OR ACIDIZES OI CE OF INTENTION TO SHOOT OR ACIDIZES OI CE OF INTENTION TO PULL OR ALTER SHUL-OFT OI CE OF INTENTION TO PULL OR ALTER SHUL-OFT OI CE OF INTENTION TO PULL OR ALTER SHUL-OFT OI CE OF INTENTION TO PULL OR ALTER SHUL-OFT OI CE OF INTENTION TO PULL OR ALTER SHUL-OFT OI CE OF INTENTION TO PULL OR ALTER SHUL-OFT OI CE OF INTENTION TO PULL OR ALTER SHUL-OFT OI CE OF INTENTION TO PULL OR ALTER SHUL-OFT OI CE OF INTENTION TO PULL OR ALTER SHUL-OFT SUBSCOURT REPORT OF EACHDONNENT. SUBSCOURT REPORT OF FALTER OF ALTER OR ALTER OF REPORT, NOTICE, OR OTHER DATA) JANUARY 21 1960 10 CE OF INTENTION TO PULL OR ALTER SHUL-OFT SUBSCOURT REPORT OF ALTER OR CASING SUBSCOURT REPORT OF ALTERORY OF ALTERORY OF ALTERORY SUBSCOURT REPORT OF ALTERORY SUBSCOURT REPO			SUBSECUENT REPORT OF WATER SHUT-OFF
Subsequent report of Altering Canada. Subsequent report of Altering Canada. Subsequent report of Altering Canada. Subsequent report of Redrilling or Repair. Subsequent report of Report. Subsequent report of Redrilling or Repair. Subsequent report of Report. Subsequent report of Redrilling or Repair. Subsequent report of Redrilling or Repair. Subsequent report of Report. Subsequent report of Redrilling or Repair. Subsequent report of Report. Subsequent report of Report of Report. Subsequent report of Report o			N 1
Subscuent report of Redelland on Repair O'LEC OF INTENTION OF SHOOT OR ACTIOIZE O'LEC OF INTENTION TO FULL OR ALTER SUBJECTION O'LEC OF INTENTION TO PULL OR ALTER SUBJECTION (REPAIR SUBJECTION NOTICE, OR OTHER DATA) JETUS 1. Is located 1100 ft. from Siline and 1150 ft. from Willing of sec. 33. JETUS 1. Is located 1100 ft. from Siline and 1150 ft. from Willing of sec. 33. A TEST 1. Is located 1100 ft. from Siline and 1150 ft. from Willing of sec. 33. DETAILS OF WORK 1. Spudded well on January h, 1960 2. Ran 3 joints 9-5/5", 32.30%, Help surface obs. on January h, 1960. 2. Ran 3 joints 9-5/5", 32.30%, Help surface obs. on January h, 1960. 3. It illed plug and pressured up to 500 pai for 30 sine. on surface obs. on January 6, 1960 - Pressure hold. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. O'LE CON	OTICE OF IN	NTENTION TO CHANGE LANS	11
SUBSEQUENT REPORT OF ABANDONMENT O' ICE OF INTENTION TO PULL OR ACTED AS AND ACTED AS AND ON HER CANADA SUBSEQUENT REPORT OF ABANDONMENT O' ICE OF INTENTION TO ABANDON HOLD (NAME ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) January 2;, 1960 I NO. 13	OTICE OF IN	NIENTICIA TO DE DELL OR REPAIR WELL	
Interpretation of the derrick floor above sea level is5746. ft. DETAILS OF WORK at names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate muddlik for general proposed work) 1. Spudded well on Januar; h, 1960 2. Ram 3 joints 9-5/5", 32.30%, it-but surface coge, on January h, 1960. 2. Ram 3 joints 9-5/5", 32.30%, it-but surface coge, on January h, 1960. 3. Prilled plug and pressured up to 500 pai for 30 sine, on surface coge, on January 6, 1960 - Pressure held. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. On pany South 2 Hard 615	OTICE OF I	NIENTION OF ACIDIZE CURVEO	
Interpretation of the derrick floor above sea level is5746. ft. DETAILS OF WORK at names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate muddlik for general proposed work) 1. Spudded well on Januar; h, 1960 2. Ram 3 joints 9-5/5", 32.30%, it-but surface coge, on January h, 1960. 2. Ram 3 joints 9-5/5", 32.30%, it-but surface coge, on January h, 1960. 3. Prilled plug and pressured up to 500 pai for 30 sine, on surface coge, on January 6, 1960 - Pressure held. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. On pany South 2 Hard 615	O ICE OF I	NTENTION TO SHOUT OF ACTORES WELL TO	1 1 2 3 1
Interpretation of the derrick floor above sea level is5746. ft. DETAILS OF WORK at names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate muddlik for general proposed work) 1. Spudded well on Januar; h, 1960 2. Ram 3 joints 9-5/5", 32.30%, it-but surface coge, on January h, 1960. 2. Ram 3 joints 9-5/5", 32.30%, it-but surface coge, on January h, 1960. 3. Prilled plug and pressured up to 500 pai for 30 sine, on surface coge, on January 6, 1960 - Pressure held. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. On pany South 2 Hard 615	O ICE OF II	NTENTION TO PULL OR ALTER COMMISSION NEW TONING	
January 29	IO ICE OF II	NTENTION TO ABANDON TELECOM	
ine elevation of the derrick floor above sea level is _5796. ft. DETAILS OF WORK 1. Spudded well on Jamary h, 1960 2. Ran 3 joints 9-5/5", 32.30%, Held surface cage, on Jamary h, 1960. Casing landed at 105.51 R		(INTINENTE ABOVE BY CHECK MARK N	ATURE OF REPORT, NOTICE, OR OTHER DATA)
A stage interest Cliffs (Cliff) (Cliff) (Cliff) (Cliff) Re elevation of the derick floor above sea level is		•	January 23, 1960
A first control of the derrick floor above sea level is 5796 ft. DETAILS OF WORK at names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indican mudding lober among points, and all other important proposed work) 1. Spudded well on January 1, 1960 2. Ran 3 joints 9-5/d*, 32-30*, 11-40 surface cage on January 1, 1960. Casing landed at 105.5! R. sl. Catd. w/100 ax reg. commit w/2* calcium chloride - Cament circulated to surface. 3. Trilled plug and pressured up to 500 psi for 30 mins. on surface cage on January 6, 1960 - Pressure helds I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. On pany Carrier 1985 as a large of the Geological Survey before operations may be commenced. On pany Carrier 1985 as a large of the Geological Survey before operations may be commenced. On pany Carrier 1985 as a large of the Geological Survey before operations may be commenced. On pany Carrier 1985 as a large of the Geological Survey before operations may be commenced. On pany Carrier 1985 as a large of the Geological Survey before operations of the G	el No	7achry is located 1100 ft. from	S line and the from W line of sec. 33.
DETAILS OF WORK at names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicat mudding Jabanaman ing points, and all other important proposed work) 1. Spudded well on January is, 1960 2. Ran 3 joints 9-5/0", 32-30", itself surface esg. on January is, 1960. Casing; landed at 105-5" R. al. Catd. w/100 ax reg. commit w/2% calcium chloride - Cament circulated to surface. 3. Urilled plug and pressured up to 500 psi for 30 mins. on surface esg. on January 6, 1960 - Pressure hold. 1 understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. on pany Grand and Case of the Case o	A Se	ec. Mil. (No.) 33 (F) (E	(Mendish)
DETAILS OF WORK ate names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding Jobe Jemen ing points, and all other important proposed work) 1. Spudded well on January h, 1960 2. Ran 3 joints 9-5/6", 32.30", indice surface cage, on January h, 1960. Casing landed at 105.5' R. als. Catd. w/100 ax reg. cament w/2% calcium chloride - Casent circulated to surface. 3. Frilled plug and pressured up to 500 psi for 30 mins. on surface cage, on January 6, 1960 - Pressure hold. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. On pany South the first Case Care and the Case of the Case of Ca	A rteo-	intered Cliffs founds	Subdivision) (State of Africary)
DETAILS OF WORK ate names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding Jobe Jemen ing points, and all other important proposed work) 1. Spudded well on January h, 1960 2. Ran 3 joints 9-5/6", 32.30", indice surface cage, on January h, 1960. Casing landed at 105.5' R. als. Catd. w/100 ax reg. cament w/2% calcium chloride - Casent circulated to surface. 3. Frilled plug and pressured up to 500 psi for 30 mins. on surface cage, on January 6, 1960 - Pressure hold. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. On pany South the first Case Care and the Case of the Case of Ca			FFRIO
DETAILS OF WORK ate names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding Jobe Jemen ing points, and all other important proposed work) 1. Spudded well on January h, 1960 2. Ran 3 joints 9-5/6", 32.30", indice surface cage, on January h, 1960. Casing landed at 105.5' R. als. Catd. w/100 ax reg. cament w/2% calcium chloride - Casent circulated to surface. 3. Frilled plug and pressured up to 500 psi for 30 mins. on surface cage, on January 6, 1960 - Pressure hold. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. On pany South the first Case Care and the Case of the Case of Ca	ne elevat	tion of the derrick floor above sea leve	el 185796. tt.
1. Spudded well on January h, 1960 2. Ran 3 joints 9-5/0", 32-30", 1-40 surface one on January h, 1960. Casing landed at 105-5' R			VOIL BOX
2. Ram 3 joints 9-5/5", 32.30", Held surface one on January h, 1960. Casing landed at 105.5' R. B. Catd. w/100 ax reg. coment w/2% calcium chloride - Cament circulated to surface. 3. Frilled plug and pressured up to 500 psi for 30 mins. on surface cage on January 6, 1960 - Pressure hald. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. On pany Court as Surface Case Case By Lincoln J. 1960 - Pressure Description D	tato names c		weights, and lengths of proposed casings; indicate mudding lobe comen
Casing landed at 105.57 %	1.		
I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. on pany South South Case Case By Manual Commenced. By Carrier J. 1980	2.	Casing landed at 105.5 % calcium chloride - Coment of	roulated to surface.
diress	3•	Orilled plug and pressured woods, on January 6, 1960 - Pr	p to 500 pai for 30 mine. on surface essure held.
diress By Constant Service By Constant	understa	and that this plan of work must receive approval in t	writing by the Geological Survey before operations may be commenced.
By Constitute	o: npany	TANKER SEE PRINT OF THESE	<u>(</u>
Solution of the teach	ddress		
Title		endnetony lev lext co	By Umodabate
			Title 17 11 ing Superinte dent
			GPO 04