



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. ST 073055  
Unit Flagood

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Flagood  
Well No. 12-0 is located 2050 ft. from TXS line and 910 ft. from W line of sec. 34  
SW 1/4 Section 34 (1/4 Sec. and Sec. No.) T-27N R-13E N.M.P.M.  
(Twp.) (Range) (Meridian)  
Totah Gallup San Juan New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5804 ft. G.L.

### DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

P.S. T.D. - 9660'  
Sand-Oil fraced with 30,000' sand and 971 Bbls. oil, flushed with 191 bbls. oil.  
Breakdown pressure - 1400'  
Maximum - 2600'  
Avg. treating pr. - 2300'  
I.S. - 31.8 bps  
dropped 50 rubber ball sealers  
5-min. shut-in - 300'  
Ran 179 lbs., 5546' of 2 3/8" tubing, landed at 5596'  
Perforated nipple - 5582-5585  
Flowing through tubing.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Asten Oil and Gas Company

Address Drawer # 570

Faradington, New Mexico

ORIGINAL SIGNED BY JOE C. SALMON  
By Joe C. Salmon

Title District Superintendent