



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office _____
Lease No. **8F-078931-0**
Unit _____
Callow Federal

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	4 1/2" casg. X
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 6, 1961

Well No. **#2** is located **2275** ft. from **{N}** line and **1810** ft. from **{E}** line of sec. **33**

SW 1/4 Sec. 33
(1/4 Sec. and Sec. No.)

29N
(Twp.)

13W
(Range)

10MPH
(Meridian)

Totah-Gallup
(Field)

San Juan
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is **5709** ft. **G.L.**

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding logs, cementing points, and all other important proposed work)

Total Depth 5622'
Plugged Back 5596'

3/5/61 - Ran & set 178 jts. (5633') of 4 1/2" 11.60# casing set @ 5628' KB, 1st stage w/150 sx 50/50 permix 4% gel followed w/100 sx 50/50 permix 2% gel, plug down 1:00 AM - DV Tool @ 1673', 2nd stage w/150 sx 50/50 permix 4% gel, plug down @ 6:15 AM. WOC - moving off drilling rig.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Southwest Production Company**

Address **162 Petr. Center Bldg.,**

Farmington, New Mexico

By **Original signed by
Carl W. Smith**

Title **Production Superintendent**