



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office _____
Lease No. **SF-078931-D**
Unit _____
Callow Federal

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 27, 1961

Well No. **#2** is located **2275** ft. from **{NW}** line and **1810** ft. from **{E}** line of sec. **33**

NW 1/4 SE 1/4 Sec. 33
(1/4 Sec. and Sec. No.)

29N
(Twp.)

13W
(Range)

NMPM
(Meridian)

Basin Dakota
(Field)

San Juan
(County or Subdivision)

New Mexico
(State & Territory)

The elevation of the derrick floor above sea level is **5709** ft. **G.L.**

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate spudding jobs, cementing points, and all other important proposed work)

3/13/61 - Moved on completion tools, drid. DV tool @ 1672 & cleaned out to 5590. Pressure test casing to 3500# & displace water w/oil. Perf. 5515-20 w/4 JPF set Baker becker @ 5475. Squeezed 500 gals 15% MCA, FND 1800# @ 2 1/2 BPM @ 2150# swab & perf. 5344-54, 5456-77 w/4 JPF. WIH w/Baker packer set @ 5415, squeezed 1,000 glas. 15% MCA. FND 1300# @ 3 BPM @ 2000#. Swab acid & load oil. SOF w/75,000# 20-40 sd & 10,300 gals oil. ATP 2800# sanded off to 3500# w/6,000# sand in form. @ 25 BPM. WIH w/bit cleaned out to 5502'. SEF w/21,000# 20-40 sd & 30,200 gals oil with adomite. ATP 3100# sanded off to 3500# w/20,000# sand in formation @ 28.1 BPM flowed & swab. Abrasive jet cut 5441 & 5471. SOF w/25,000# 20-40 sd & 50,900 gals. oil w/2300# adomite. ATP 3000# NTP 3500# @ 27.2 BPM. SI Press. 1500#. Set bridge plug @ 5420'. Abrasive jet cut 5409 & 5379. SOF 12,000# 20-40 sd & 18,000 Gals oil plug @ 5420'. ATP 2700# ATP 2800# sanded off. WIH w/bit cleaned out to 5420'.
...operations may be commenced.