

(SUBMIT IN TRIPLICATE)

Indian Agency Window Rock, Ariz.

Sec. 36	
129N 118W	

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Havajo
Allottee Havajo Tract (2)
Lease No. 14-20-603-3025

SUNDRY NOTICES AND REPORTS ON WELLS

RECEIVED

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	JUL 12 1963
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIRING	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	Subsequent Report for squeezing lost circulation below 7" casing	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 9, 1963

Well No. 1 is located 1980 ft. from N line and 1980 ft. from E line of sec. 36
NW 36, Sec. 36 29N 118W NMPM
(14 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Pajarito Area San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5247 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

7-2-63 - Squeezed 259' open hole below 7" csg. 6196' to 6485', w/100 sacks reg. cement. Pumped 3 bbls. water into formation @ 900# press. 15.8# slurry. Displaced cement w/49 bbls. fresh water, Max. press. 900#. Drill pipe on slight vacuum. Drilling out cement, and will drill ahead.

7-7-63 - Squeeze lost circulation zone in open hole below 7" csg. 6196' to 6441'. Pumped in 3 bbls. mud @ 1500# press., injection rate 9 bbls. per min.. Squeezed w/100 sacks reg. cement, mixed w/12.5# Gelsolite per sack, 14.1# slurry. Displaced cement w/46 bbls. mud. Left two bbls. cement in 7" csg. w/400# standing press. Drilled 355' firm cement, lost circulation @ 6403', lost approx. 60 bbls. On trip out of hole to squeeze.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Amerada Petroleum Corporation

Address Box 1469

Durango, Colorado

247-5353

By D. B. Helbrook
Title Foreman



