(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Agency Window-Rock,	APL
Mavajo	
Allottee Havaje Treet #25)
Lease No. 14-20-603-5025	

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INT	TENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INT	TENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	1 3
NOTICE OF INT	TENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INT	TENTION TO REDRILL OR REPAIR WELL.	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	Y Y
OTICE OF INT	TENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	<u>v 4 252 (</u> 2572)
OTICE OF INT	TENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY.	
OTICE OF IN	TENTION TO ABANDON WELL		
		Subsequent Report for Squeezing	¥
	(INDICATE ABOVE BY CHECK	(MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)	
			, 19 .63
		(NI) (E')	
ell No	is locatedf	ft. from $\left\{\begin{matrix} \mathbf{S} \\ \mathbf{S} \end{matrix}\right\}$ line and 1900 ft. from $\left\{\begin{matrix} \mathbf{E} \\ \mathbf{W} \end{matrix}\right\}$ line of sec.	96
			FR
W SEA SH	Ma Salto.)	(R)	
		(materialis)	~ <i>~\\\\</i> \\
njerito	diela	County or Subdivision) (State or Territory)	,····
	(1.1.1.2)	0,,	30.
ne elevatio	on of the derrick floor above s	sea level isft.	1963
			<i>y</i>
		\ 0/0	~ C~ /
		ETAILS OF WORK	T. SCOM.
	DI	ETAILS OF WORK	T. 3 COM.
tate names of	D] and expected depths to objective sands; si ing points, ar	ETAILS OF WORK show sizes, weights, and lengths of proposed casings; indicate mudding and all other important proposed work)	
ate names of	and expected depths to objective sands; at ing points, as a squeezed lost circ. so w/100 sacks reg. comen a 5 bhis. per min., pu cement w/38 bbis. mud.	ETAILS OF WORK thow sizes, weights, and lengths of proposed casings; indicate mudding and all other important proposed work) one in open hole below 7" eag. from 6196" at w/25 Gilsonite per sack. Pumped in 5 amping rate 1200 press., 13.3 Slupry. It formation squeezed w/4200 standing pressures. Trip in hole w/62" bit to drill of	to 6457', bblo. and displaced
ate names of	and expected depths to objective sands; at improvints, are squeezed lost eire. se w/100 sacks reg. eeman 5 5 bhls. per min., pu cement w/38 bbls. mud. Reversed out 6 bbls. e Gilsenite per sack, pu pumping rate 8 500% pr w/52 bbls. water, Hax.	one in open hole below 7" esg. from 6196' at w/25# Gilsonite per sack. Pumped in 5 suping rate 1200# press., 13.3# Slurry. D . Formation squeesed w/4200# standing pre	to 64.57', bbls. and pisplaced pas pement. per min., 6250' t tool
Ate names of ./10/63 -	and expected depths to objective sands; all impoints, at a squeezed lost eire. se w/100 sacks reg. eemen e 5 bhls. per mim., pu cement w/38 bbls. mud. Reversed out 6 bbls. e Gilsonite per sack, pu pumping rate e 500 pr w/52 bbls. water, Nax. eleced w/press. on dri	one in open hole below 7" esg. from 6196' at w/25f Gilsonite per sack. Pumped in 5 amping rate 1200f press., 13.3f Slurry. D. Formation equeesed w/4200f standing pressure. Trip in hole w/6½" bit to drill come from 6196' to 6841', w/100 sx. reg. outped 4 bbls. and in formation \$ 4 bbls. ress., 13.3f Slurry. Displaced coment to Press. 2500f, Standing Press. 700f. Left pipe. Released tool & trip cut of hol	to 64.57', bbls. and pisplaced les lement. lement w/25# per min., 6250' t teel
110/63 -	and expected depths to objective sands; all impoints, at a squeezed lost eire. se w/100 sacks reg. eemen e 5 bhls. per mim., pu cement w/38 bbls. mud. Reversed out 6 bbls. e Squeezed lost eire. se Gilsonite per sack, pu pumping rate e 500% pr w/52 bbls. water, Nax. eleced w/press. on dri	one in open hole below 7" esg. from 6196' at w/25 Gilsonite per sack. Pumped in 5 amping rate 1200 press., 13.3 Slurry. It is formation equeesed w/4200 standing present. Trip in hole w/62" bit to drill one from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. one from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. of following from 6196' to 6841', w/100 sx. reg. of following from 6196' to 6841', w/100 sx. reg. of following from 6196' to 6841', w/100 sx. reg. of following from 6196' to 6841', w/100 sx. reg. of following from 6196' to 6841', w/100 sx. reg. of following from 6196' to 6841', w/100 sx. reg. of following from 6196' to 6841', w/100 sx. reg. of following from 6196' to 6841', w/100 sx. reg. of following from 6196' to 6841', w/100 sx.	to 64.57', bbls. and displaced les lement. lement w/25# per min., 6250' t teel
10/63 -	and expected depths to objective sands; all impoints, at a squeezed lost eire. se w/100 sacks reg. eemen e 5 bhls. per mim., pu cement w/38 bbls. mud. Reversed out 6 bbls. e Squeezed lost eire. se Gilsonite per sack, pu pumping rate e 500% pr w/52 bbls. water, Nax. eleced w/press. on dri	one in open hole below 7" esg. from 6196' at w/25 Gilsonite per sack. Pumped in 5 amping rate 1200 press., 13.3 Slurry. It is formation equeesed w/4200 standing present. Trip in hole w/62" bit to drill one from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. one from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. of following from 6196' to 6841', w/100 sx. reg. of following from 6196' to 6841', w/100 sx. reg. of following from 6196' to 6841', w/100 sx. reg. of following from 6196' to 6841', w/100 sx. reg. of following from 6196' to 6841', w/100 sx. reg. of following from 6196' to 6841', w/100 sx. reg. of following from 6196' to 6841', w/100 sx. reg. of following from 6196' to 6841', w/100 sx. reg. of following from 6196' to 6841', w/100 sx.	to 64.57', bbls. and displaced les lement. lement w/25# per min., 6250' t teel
1 understand	and expected depths to objective sands; all impoints, are squeezed lost eire. see w/100 sacks reg. eemen e 5 bbls. per mim., pu cement w/38 bbls. mud. Reversed out 6 bbls. e Glasmite per sack, pu pumping rate e 500% pr w/52 bbls. water, Max. elected w/press. on dri Drilling ahead. I that this plan of work must receive appr Amerada-Petroloum Cory	one in open hole below 7" esg. from 6196' at w/25 Gilsonite per sack. Pumped in 5 amping rate 1200 press., 13.3 Slurry. It. Formation equeesed w/4200 standing present. Trip in hole w/62" bit to drill one from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. on the following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/100 sx. reg. on following from 6196' to 6841', w/	to 64.57', bbls. and displaced les lement. lement w/25# per min., 6250' t teel
1 understand	and expected depths to objective sands; all impoints, are squeezed lost eire. see w/100 sacks reg. eemen e 5 bbls. per mim., pu cement w/38 bbls. mud. Reversed out 6 bbls. e Glasmite per sack, pu pumping rate e 500% pr w/52 bbls. water, Max. elected w/press. on dri Drilling ahead. I that this plan of work must receive appr Amerada-Petroloum Cory	one in open hole below 7" esg. from 6196' at w/25f Gilsonite per sack. Pumped in 5 suping rate 1200f press., 13.3f Slurry. It is formation squeezed w/4200f standing pressure. Trip in hole w/6½" bit to drill one from 6196' to 6841', w/100 sx. reg. on the following from a finite from 6196' to 6841', w/100 sx. reg. on the following from	to 64.57', bhis. and cisplaced sec cement w/25# per min., 6250' 't tool menced.
Ate names of	and expected depths to objective sands; all impoints, at a squeezed lost eire. se w/100 sacks reg. eemen e 5 bhls. per mim., pu cement w/38 bbls. mud. Reversed out 6 bbls. e Squeezed lost eire. se Gilsonite per sack, pu pumping rate e 500% pr w/52 bbls. water, Nax. eleced w/press. on dri	one in open hole below 7" esg. from 6196' at w/25f Gilsonite per sack. Pumped in 5 suping rate 1200f press., 13.3f Slurry. It is formation squeezed w/4200f standing pressure. Trip in hole w/6½" bit to drill one from 6196' to 6841', w/100 sx. reg. on the following from a finite from 6196' to 6841', w/100 sx. reg. on the following from	to 64.57', bhis. and cisplaced sec cement w/25# per min., 6250' 't tool menced.
/10/63 - /11/63 i understand ompany	and expected depths to objective sands; all impoints, are squeezed lost eire. see w/100 sacks reg. eemen e 5 bbls. per mim., pu cement w/38 bbls. mud. Reversed out 6 bbls. e Glasmite per sack, pu pumping rate e 500% pr w/52 bbls. water, Max. elected w/press. on dri Drilling ahead. I that this plan of work must receive appr Amerada-Petroloum Cory	one in open hole below 7" esg. from 6196' at w/25f Gilsonite per sack. Pumped in 5 suping rate 1200f press., 13.3f Slurry. It. Formation equeesed w/4200f standing present. Trip in hole w/6½" bit to drill come from 6196' to 6841', w/100 sx. reg. one from 6196' to 6841', w/100 sx. reg. o	to 64.57', bhis. and cisplaced sec cement w/25# per min., 6250' 't tool menced.
I understand	and expected depths to objective sands; at impoints, as a squeezed lost cire. See w/100 sacks reg. cement s 5 bhls. per mim., pu cement w/38 bbls. mud. Reversed out 6 bbls. co. Squeezed lost cire. See Qilsenite per sack, pu pumping rate 9 500% pr w/52 bbls. water, Nax. cleed w/press. on dri Drilling ahead. I that this plan of work must receive appr morada. Petroloum Cory.	one in open hole below 7" esg. from 6196' at w/25f Gilsonite per sack. Pumped in 5 suping rate 1200f press., 13.3f Slurry. It is formation squeezed w/4200f standing pressure. Trip in hole w/6½" bit to drill one from 6196' to 6841', w/100 sx. reg. on the following from a finite from 6196' to 6841', w/100 sx. reg. on the following from	to 64.57', bhis. and cisplaced sec cement w/25# per min., 6250' 't tool menced.