

NEW MEXICO OIL CONSERVATION COMMISSION
GAS WELL TEST DATA SHEET - SAN JUAN BASIN

(TO BE USED FOR FRUITLAND, PICTURED CLIFFS, MESAVERDE, & ALL DAKOTA
EXCEPT BARKER DOME STORAGE AREA)

Pool Astec Pictured Cliffs Formation Pictured Cliffs County San Juan
Purchasing Pipeline Southern Union Gas Company Date Test Filed 4-24-56

Operator Southern Union Gas Company Lease Wilson Well No. 1
Unit H Sec. 31 Twp. 29N Rge. 10W Pay Zone: From 1796 To 1840
Casing: OD 5-1/2" WT. 15.5# Set At 1796 Tubing: OD 1" WT. 1.7# T. Perf. _____
Produced Through: Casing IX Tubing _____ Gas Gravity: Measured .667 Estimated _____
Date of Flow Test: From 3/24/56 To 3/31/56 * Date S.I.P. Measured 12-30-55
Meter Run Size 4" Orifice Size 1-1/4" Type Chart Normal Type Taps Flange

OBSERVED DATA

Flowing casing pressure (Dwt) _____ psig + 12 = _____ psia (a)
Flowing tubing pressure (Dwt) _____ psig + 12 = _____ psia (b)
Flowing meter pressure (Dwt) _____ psig + 12 = _____ psia (c)
Flowing meter pressure (meter reading when Dwt. measurement taken):
Normal chart reading _____ psig + 12 = _____ psia (d)
Square root chart reading (_____) ² x spring constant _____ = _____ psia (d)
Meter error (c) - (d) or (d) - (c) _____ ± _____ = _____ psi (e)
Friction loss, Flowing column to meter:
(b) - (c) Flow through tubing: (a) - (c) Flow through casing _____ = _____ psi (f)
Seven day average static meter pressure (from meter chart):
Normal chart average reading 215 psig + 12 = 227 psia (g)
Square root chart average reading (_____) ² x sp. const. _____ = _____ psia (g)
Corrected seven day avge. meter press. (p_f) (g) + (e) _____ = 227 psia (h)
P_t = (h) + (f) _____ = 227 psia (i)
Wellhead casing shut-in pressure (Dwt) 610 psig + 12 = 622 psia (j)
Wellhead tubing shut-in pressure (Dwt) 610 psig + 12 = 622 psia (k)
P_c = (j) or (k) whichever well flowed through _____ = 622 psia (l)
Flowing Temp. (Meter Run) 56 °F + 460 _____ = 516 °Abs (m)
P_d = 1/2 P_c = 1/2 (l) _____ = 311 psia (n)

FLOW RATE CALCULATION

Q = 108 X $\left(\frac{\sqrt{(c)}}{\sqrt{(d)}} = \frac{\text{None}}{\text{None}} \right)^* = \text{108 MCF/da}$
(integrated)

DELIVERABILITY CALCULATION

D = Q 108 $\left[\frac{P_c^2 - P_d^2}{P_c^2 - P_w^2} \right]^{0.85} = \text{.88424} = \text{96 MCF/da.}$

SUMMARY

P_c = 622 psia
Q = 108 Mcf/day
P_w = 227 psia
P_d = 311 psia
D = 96 Mcf/day

Company Southern Union Gas Company
By L. S. Muesink
Title Jr. Petroleum Engineer
Witnessed by _____
Company _____

* This is date of completion test.
* Meter error correction factor

REMARKS OR FRICTION CALCULATIONS

GL	(1-e ^{-S})	(FcQ) ²	(FcQ) ² (1-e ^{-S})	P _t ²	P _t ² + R ²	P _w
			R ²	(Column i)		

Friction Loss Negligible

OK



OIL CONSERVATION COMMISSION		
AZTEC DISTRICT OFFICE		
No. Copies Received		3
DISTRIBUTION		
	NO. FURNISHED	
Operator		
Santa Fe	1	
Proration Office		
State Land Office		
U. S. G. S.	1	
Transporter		
File	1	✓