

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF-078926

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Gallegos Canyon Unit-

8. FARM OR LEASE NAME

9. WELL NO.

87

10. FIELD AND POOL, OR WILDCAT

Kutz West Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 35-T29N-R13W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

1. OIL ☐ WELL GAS ☒ WELL OTHER ☐ Re-entry

2. NAME OF OPERATOR

Energy Reserves Group, Inc.

3. ADDRESS OF OPERATOR

P. O. Box 3280, Casper, Wyoming 82602

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1650' FNL, 1850' FWL (NW SE NW)

14. PERMIT NO.

15. ELEVATIONS (Show whether DV, ST, GR, etc.)

5840' GRD

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) Re-enter P & A Well ☒PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

This well was drilled and completed in the Gallup formation in 1960. A DV cementing tool was set at 1902' and 250 sacks of cement were circulated across the Pictured Cliffs interval. The well was plugged in April, 1965, leaving all the casing in the hole.

It is proposed to re-enter this well and drill out any necessary cement plugs to 1800'+. A drillable bridge plug will be set at 1750'+ and the Pictured Cliffs formation perforated, tested and if commercial, put on production.

18. I hereby certify that the foregoing is true and correct

SIGNED

Dean B. Barnes

TITLE

District Production Engineer

Rocky Mountain District

DATE September 20, 1976

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: