

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. SP 678931-2  
Unit \_\_\_\_\_

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL _____	SUBSEQUENT REPORT OF WATER SHUT-OFF _____
NOTICE OF INTENTION TO CHANGE PLANS _____	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING _____
NOTICE OF INTENTION TO TEST WATER SHUT-OFF _____	SUBSEQUENT REPORT OF ALTERING CASING _____
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL _____	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR _____
NOTICE OF INTENTION TO SHOOT OR ACIDIZE _____	SUBSEQUENT REPORT OF ABANDONMENT _____
NOTICE OF INTENTION TO PULL OR ALTER CASING _____	SUPPLEMENTARY WELL HISTORY _____
NOTICE OF INTENTION TO ABANDON WELL _____	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

U. S. GEOLOGICAL SURVEY  
WASHINGTON, NEW MEXICO

March 13, 1961

USA Glenn E. Callow

Well No. 16 is located 330 ft. from N line and 550 ft. from W line of sec. 27

SW 1/4 Section 27 29 N 13 W R. 1, 2, 3, 4  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Totah Valley San Juan New Mexico  
(Field) (County or Subdivision) (State or Territory)


The elevation of the ground level above sea level is 5390 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Running and cementing surface casing as follows:

Run five joints, 142 feet, casing, 2-5/8 inch, 84#, mile, 3-55 and set at 155 feet. Cemented with 125 sacks regular 24 Gulg. Circulated cement to surface. Plug down 11:00 p.m. 3-5-61. WAS 12 hours. Pressure tested casing to 750 pounds for 30 minutes. Pressure held o.k.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Sumco Corporation

Address P. O. Box 1724

Durango, Colorado

By L. B. Hunt

Title District Production Superintendent