



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. ST 073005
Unit Hagood

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	RECEIVED
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Hagood

Well No. 25-6 is located 525 ft. from N line and 300 ft. from E line of sec. 30

30 section 30
($\frac{1}{4}$ Sec. and Sec. No.)

25N 13
(Twp.) (Range)

N.A.P.M.
(Meridian)

Totah Gallup
(Field)

San Juan
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 5011 ft. Gal.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Total depth- 5524 P.S.L.D. 5591

Run logs: top of fractured cliffs-1447, joint layout-3408, Gallup-5132

Perforated with 4 shots per foot from 5468-5471 and free notch at 5491

Set 1 1/2 in., 5025' of 4 1/2" casing, landed at 5493'

D.V. tool- 1641

Cemented 1st stage with 250 sz., 2nd stage with 150 sz.

drilled cement 7/24/61

tested for 3 hrs., with 300 pressure

Pipe clay.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Astec Oil & Gas Company

Address Tractor # 570

Farmington, New Mexico

ORIGINAL SIGNED BY JOE C. SALMON
By Joe C. Salmon
Title District Superintendent