

U. S. LAND OFFICE Santa Fe SERIAL NUMBER LEASE OR PERMIT TO PROSPECT

1963 UNITED STATES 14-20-603-2014 OIL COMPROMMENT OF THE INTERIOR DEGE VE

LOG OF OIL OR GAS WELL GEOLOGICAL SURVEY W MEXICE

		ELL CORRE					- - -				FA	RMINGTON, NE	
Company James R. Pickett							Addre	ess	P. O. Box	x 268, P	hoemix	Arizona	
Lessor	or Tra	ctNa	vajo]	indian			Field		Wildcat	Stat	. Nes	v Mexico	
Well N	1. 	Sec.	26 T.	29N R	15W M	erid	ian M	(PM	C	ounty &	dan Jus	Mexico	
Locati	on	60 ft. [X.]	of	Line a	nd 595	ft. []	E of	Lin	ne of Sect:	Lon 26	Flor	ation 5371	
T	he infor	mation give determi	ven her	ewith is	s a compl	lete	and corre	ct re	ecord of the	well and a	ll work	done thereon	
		ebruary		_	8	Sign	ned 100	a	n 22.				
						, ·	-6.41	,,		openiti:	is reon	ogist	
									above date.	Die State and	_	4	
Comm	encea a	rilling	o or a constant							Buriar	7.3	, 19 63 .	
				OI			SANDS of gas by G		ZONES				
No. 1,	from	·	1	to					m	t	0		
							No. 4, from to						
No. 3,	from		1	to	~~~~~	-	No. 6	, fro	m	to)		
No. 1,	1340	1 	to	3272		No. 4, from to							
CASING RECORD													
Size casing	Weight per foot		per	Make	Amount	;]	Kind of shoe	Cut	and pulled from	Perfo	Т	Purpose	
		_		THE SHAME SE	19 1 Ba ler	, stat	Carl da r w		_	From-	To-	_	
. الشاهات سانونونونستا			علماة المالانة والم	المشتشا فالتكافا بفي		ALLE:	BULL CHRISTING	# 364 EV 3	in it it is an are	ME OF CIAN THERE	PROTECT :	or eather.	
	78 3 Je 62 C	. Hestimne	rtance io	p paxe a c	omolete ki	istor	v of the well	1,1	ease state in Co	full the date	g of redri	ling, together	
					PORY C	Э¥4	OIL-OR-(1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	WELL		5. GOVERNITER	13 3 9 c 19	
MUDDING AND CEMENTING RECORD													
* Size	Where	set	Number s	acks of cer	nent	N	Tethod used		Mud gravity	Ar	nount of m	nud used	
8 5/	8 123	3	100)		Ci	rculated						
							[
					1					1			
							ND ADAP		RS				
Heaving	g plug–	-Material		<u> </u>						Depth set			
							i						
							NG RECO						
Size		Shell used	E	xplosive us	ed	Qua	ntity D	ate	Depth shot	;	Depth clear	ned out	

Rotary	tools w	ere used fr	om	!			LS USED	feet.	and from		foot to	feet	
Cable to	ools wer	e used fron	n	U	feet t	to -	plo	feet	, and from		foot to	foot	
							ATES	1000	, who hom		1660 00 .	1001	
• • • • • • • • • • • • • • • • • • •	Febr	ary 5,	,	¹⁹ 63			Put to	prod	lucing	·2::- *		, 19,4	
The	e produ	ction for	the first	t 24 hou	ırs was		Put to producing P & A 2-3 , 1963 barrels of fluid of which% was oil;%						
emulsion;% water; and4% sediment.							Gravity, °Bé						
If g	gas well	, cu. ft. pe	r 24 ho	urs			Gallons	gaso	oline per 1,00				
		sure, lbs. p		1							Ü		
				i i		MP	LOYEES						
Driller							, Driller						
·•	:			Driller			, Driller						
						AT	ON REC	ORD					
FROM	M— 	ТО-	-	TO	TAL FEET			<u>-</u>	FOR	MATION			
0		78		78	3		Kilonia Tarani						
78		412		33	34		with tie	ghrt .	gray fine m., gray c	grained	55		
·		·		The state of the s	· ··•		scattere ss.	d c	cals , gray	y tight	fine and	grained	
412		610		15	98				iffs fm.,	gray fir	ne grai	ined	
610	0 1340 730			30		Lewis fm., gray shale grading to very dense sil. shaly ss.							
1340 3272			1932			Mosayurd	e o	maly ss. m., gray i md carbons	ine grai	med si	1. to		
3272 4270						scals.							
,						bedded a	ilt	gray earb stomes.					
427 0 4678			408			delinp f	m.,	gray calc	arecus s	halesw	rith		
			!				POCENTIES.	u#G	sandstone	and sil	eno s er.	•	
	1		!										
			į										

MONGRADION

16-43094-5

TO-