

U. S. GOVERNMENT PRINTING OFFICE

TE 55071.

WRITTEN TESTS : None made.

Fert. 5289-981, casing B zone, w/2 holes per ft., broke perf., down with 20 bbls. oil.
 pump in 85 bbls. lease crude w/ 1/2 sand per gal. cut 250 bbls BDA on perf., treated
 perf. with 8000# 20-40 sand & 4000# 10-20 sand w/ 1/3, 1/6 gals lease crude, w/250 gals
 BDA, max press 2900#, min 2500#. Washed and flowed well to recover all load oil. Set
 pumping unit and pumped well at rate of 140 bbl per day. Well on pump test from 5-30-61
 to 7-18-61. Kill well, pull rods and tubing. Fert. 5234-46, w/2 shots per ft., bridge
 plug set at 52601. Perf. 5234-46 is lower horizon zone. Spotted 250 gals HSA
 across perf., gas perf. w/30,000 gals crude, mixed w/3000# admats & 20,000# 20-40
 water wet sand, followed with 10,000# 10-20 water wet sand. Max press 2900#, min 2600#.
 Flow well to test, to all load oil. Test 24 hrs. perf. 5234-46, rec. 220 bbl on
 1/2" choke. Kill well, perf. 5206-181 in upper horizon zone. Bridge plug set at 52264
 well completed as oil well flowing through 1" choke at rate of 312 BO & 0 BW PD on 24
 hour test. Perfs. at 5206-181, 5234-46, 5289-981. End May 221.