



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office **Santa Fe**  
Lease No. **078931-B**  
Unit \_\_\_\_\_

SUNDRY NOTICES AND REPORTS ON WELLS

|   |   |                                     |
|---|---|-------------------------------------|
| NOTICE OF INTENTION TO DRILL.....                   | SUBSEQUENT REPORT OF WATER SHUT-OFF.....        | <input checked="" type="checkbox"/> |
| NOTICE OF INTENTION TO CHANGE PLANS.....            | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... | <input checked="" type="checkbox"/> |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....     | SUBSEQUENT REPORT OF ALTERING CASING.....       | <input checked="" type="checkbox"/> |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR..... | <input checked="" type="checkbox"/> |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....        | SUBSEQUENT REPORT OF ABANDONMENT.....           | <input checked="" type="checkbox"/> |
| NOTICE OF INTENTION TO PULL OR ALTER CASING.....    | SUPPLEMENTARY WELL HISTORY.....                 | <input checked="" type="checkbox"/> |
| NOTICE OF INTENTION TO ABANDON WELL.....            |   |                                     |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 24, 1959

WMA Glen K. Callow

Well No. **8** is located **390** ft. from **N** line and **1370** ft. from **E** line of sec. **27**

**SE 1/4 of Sec. 27**

**29N**

**13W**

**10PM**

(1/4 Sec. and Sec. No.)

(Twp.)

(Range)

(Meridian)

**Unfractured**

**San Juan**

**New Mexico**

(Field)

(County or Subdivision)

(State or Territory)

**ground level**

The elevation of the derrick floor above sea level is **5392** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We wish to report the running and cementing of oil string.

1. Drill 8 3/4" hole to 6030'.
2. Run 5948' of 7" OD, 20#, and 23#, J-55, STAC casing set at 5960' with float collar, float shoe and cement stage collar at 1463' (123' below base of Pictured Cliffs).
3. Cemented 1st stage with 175 cu 50-50 Bimax "A" 1/4 cu. ft. of Stratacrete "6" per sack. Opened stage collar and cemented 2nd stage with 45 cu regular cement 7/10/59.
4. Run Temperature Survey. Located top of cement at 1125'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Tennessee Gas Transmission Company**

Address **P. O. Box 1714**

**Durango, Colorado**  
Attention: **Production Department**

**R. H. Walker**

By **R. H. Walker**  
**District Production Dept.**

Title \_\_\_\_\_

