STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

perator		TENNECO OIL	CO.	Le2se	CAL	LOW		We! No.		
ocation f Well: U	nit P	Sec <u>27</u> 7	wp. 29N	Rge. <u>1</u>	.3W		Cour	nry SAN	JUAN	
	NAME OF RESERVOIR OR POOL			TYPE OF PROD. (Of) or Gas)		METHOD OF PROD. (Flow or Art. LH1)			PROD. MEDIUM (Tbg. or Csg.)	
Upper ompletion	GALLUP			GAS	GAS		FLOW		TUBING	
Lower	BASIN DAKOTA			GAS	GAS		FLOW		TUBING	
			PRE-FLO	W SHUT-IN P	RESSURE	DATA				
Upper	our, date sh	าน1-เก	Length of time shut	Hin	Si press, psig			Stabilized? (Yes or No)		
ompletion:	12:30	pm 4-27-87	72 hours		80				yes	
Lower	our, date sh	nut-in	Length of time shut		Si press. psig		- I		Stabilized? (Yes or No)	
ompletion	12:30) pm 4-27-87	72 hours	<u> </u>	1 20)		<u> </u>	/es	
				FLOW TEST	NO. 1	 				
inimenced a	i (hour, date	•)* 9:00 am 4			Zone pr	oducing (Upper	pper or Lower):] OWEY			
TIME (hour, date)		LAPSED TIME SINCE*	PRESS Upper Completion	Lawer Completion	•	ZONE		REMARKS		
2:30	pm								· · · · · · · · · · · · · · · · · · ·	
5-1-8		29½ hours	800	360						
8:00 am 5-2 - 87		47 hours	800	355						
							- .			
					 					
					-					
· · · · · · · · · · · · · · · · · · ·					ļ					
-						ı				
					<u> </u>		 			
'roductioi	n rate di	uring test								
Oil:		BOP!	D based on	Bbls. i	n	Hours.		Grav	GOR	
Gas:				PD; Tested thr			ē			
				EST SHUT-IN P						
110000	lour, date s	shut-in	Length of time shu		SI press. p			Stabilized	? (Yes or No)	
Completion	Upper									
Lower	i i			ut⊣n	Si press. 5	mo Berri		Stabilized? (Yes or No)		
Completion			<u> </u>		1 1					
					દ	MAY	0 71987.	لنا		
		,								
		,				The hearty	M. DI	V.]		
				<i>(C</i>		, Di	ST. 3	A		

(Continue on reverse side)

FLOW TEST NO. 2

ommenced at (hour, d	ate)中中		Zone producing (Upper or Jower)						
TIME	LAPSED TIME	PRESSURE		PROD. ZONE					
(hour, date)	SINCE **	Upper Completion	Lower Completion	TEMP,	REMARKS				
		-							
	+		<u> </u>						
<u> </u>		- 							
<u> </u>									
			4	1					
Production rate	during test				· ·				
Oil:	BOI	PD based on	Bhls in	Hours	Grav GOR				
325:		MCI	FPD: Tested thru	(Orifice or Meter	r):				
Cemarks:									
					-				
hereby certify	that the informa-	ion bassia sansii			st of my knowledge.				
Approved		107 1987	19 (Operator TE	NNECO OIL CO.				
New Mexico (Dil Conservation	Division			JOHN CARTER				
	Original Siane	d by CHARLES GHO	EON	By (Ditter	JUHN CARTER				
Ву		, connects GNU		Title	AGENT				
Title	DELOTE CITY OF A	BAS INSPECTOR, DIS	i. #3	Date	5-5-87				

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packet or the tubing have been disturbed. Term shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so porified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such ten shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage ten, a gas well is being flowed to the autosphere due to the lack of a pipeline connection the flow period shall be three bours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even shough no leak was indicated during Flow Ten No. 1. Procedure for Flow Ten No. 2 is to be the same as for Flow Ten No. 1 except

- that the previously produced zone shall remain shur-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at bourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Axter District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packet Leakage Test Form Revised 10-01-75 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).