Form 9-331a (Feb. 1951)					
	٠.				

(SUBMIT IN TRIPLICATE)

Land Office	Santa Fe
Lease No	080962

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Unit Gallegos Canyon Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL NOTICE OF INTENTION TO CHANGE PLAMS. NOTICE OF INTENTION TO THE SAME. NOTICE OF INTENTION TO THE SAME. NOTICE OF INTENTION TO REDBILL OR REPAIR WELL NOTICE OF INTENTION TO REDBILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE. NOTICE OF INTENTIO		
NOTICE OF INTENTION TO CHANGE PLANS. NOTICE OF INTENTION TO TEST WATER SHUT-OFF NOTICE OF INTENTION TO TEST WATER SHUT-OFF NOTICE OF INTENTION TO TEST WATER SHUT-OFF NOTICE OF INTENTION TO SHOOT OR ACIDIZE. NOTICE OF INTENTION TO SHOOT OR ALTER CASING. NOTICE OF INTENTION TO SHOOT ALTER CASING.	NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTERVION TO TEST WATER SHUT-OFF NOTICE OF INTERVION TO REDRILL OR REPAIR WILL NOTICE OF INTERVION TO REDRILL OR REPAIR WILL NOTICE OF INTERVION TO PULL OR ALTER CASING NOTICE OF INTERVION TO PARK INTERVION TO PULL OR ALTER NOTICE OF INTERVION TO PARK INTERVION TO PULL OR ALTER NOTICE OF INTERVION TO PULL OR ALTER NOTICE OF INTERVION TO PARK INTERVION TO PARK INTERVION TO PARK INTERVION TO PULL OR ALTER NOTICE OF INTERVION TO PARK INTER	1	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO SHOOT OR ACIDIZE. NOTICE OF INTENTION TO PULL OR ALTER CASING. MOTICE OF INTENTION TO PULL OR ALTER CASING. MOTICE OF INTENTION TO ABANDON WELL (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER BATA) Farmington, New Mexico. May 10 , 1956. Well No. 74 is located 1450 ft. from Siline and 1850 ft. from William of sec. 29 SW/4 of Section 29 T-29-N R-12-W NMPK ((State names of and expected depths to objective anales show sizes, weights, and langths of proposed casings; indicate mudding jobs, coment ing points, and all other important proposed work) On May 2, 1956, this well was perforated with two jet shots per foot from 120 1250 to 1270 feet. On May 3, 1956, this well was sand-water fracked through the above perforations with 20,000 gallons water, 30,000 pounds and average injection rate 44 by 13 per minutes. Preliminary test, 2684 MCF per day. Lunderstand that this plan of work must receive approval in writing by the Geological Survey before constitution into the comment. A May 3, 1956, this plan of work must receive approval in writing by the Geological Survey before constitution into the comment. JUN 22 1356 OR COM. DIST 3 Lunderstand that this plan of work must receive approval in writing by the Geological Survey before constitution into the comment.		SUBSEQUENT REPORT OF ALTERING CASING.
NOTICE OF INTENTION TO PULL OR ALTER CASING NOTICE OF INTENTION TO ABANDON WELL (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER BATA) Farmington, New Mexico May 10 1956. Well No. 74 is located 1450 ft. from Sime and 1850 ft. from Willing of sec. 29 SW/L of Section 29 T-29-N R-12-W NMPM (Range) (Range) West Kutz-Platured Cliffs San Juan New Mexico (State of Territory) The elevation of the derrick floor above sea level is 5358 ft. DETAILS OF WORK (State names of and expected depths to objective sands; show discs, weights, and langths of proposed casings; indicate mudding jobs, cament ing points, and all other important proposed worth) On May 2, 1956, this well was perforated with two jet shots per foot from 120 1250 to 1270 feet. On May 3, 1956, this well was sand-water fracked through the above perforations with 20,000 gallons water, 30,000 pounds sand. Formation broke at 2600 pounds. Treating pressure was 1100 pounds and average injection rate 144 have 13 per minutes. Preliminary test, 2684 MCF per day. Lunderstand that this plan of work must receive approval in writing by the Geological Survey before open tions may be communiced. Company Significant Street COMPANY Address 1. C. MA SCOMPANY Address 1. C. MA SCOMPANY	NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
Well No. 74 is located 1450 ft. from Stime and 1850 ft. from White of sec. 29 SW/4 of Section 29 T-29-N R-12-W NMPM (Mercian) West Kutz-Pictured Cliffs San Juan New Mexico (Field) The elevation of the derrick floor above sea level is 5258 ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding Jobs, cament ing points, and all other important proposed work) On May 2, 1956, this well was perforated with two jet shots per foot from 120 1250 to 1270 feet. On May 3, 1956, this well was sand-water fracked through the above perforations with 20,000 gallons water, 30,000 pounds and average injection rate 44 by 13 per minutes. Preliminary test, 2684 MCF per day. I understand that this plan of work must receive approval in writing by the Geological Survey before one atom may be communicated. Company STAINTIN CH & CAS COMPANY Address 1 Company STAINTIN CH & CAS COMPANY Address 1 Company STAINTIN CH & CAS COMPANY Address 1 Company STAINTIN CH & CAS COMPANY Address 1 Company STAINTIN NEW MAY STAINTING TO THE ADDRESS TO THE STAINTING TO THE		
Well No		SUPPLEMENTARY WELL HISTORY
Well No. 74 is located 1450 ft. from Siline and 1850 ft. from Willine of sec. 29 SW/4 of Section 29 T-29-N R-12-W NMPM (A Sec. No.) (Twp.) R-12-W NMPM (County or Subdivision) (State or Territory) West Kutz-Pictured Cliffs San Juan New Mexico (State or Territory) The elevation of the derrick floor above sea level is 5358 ft. DETAILS OF WORK (State names of and expected depths to objective sands; show size, weights, and lengths of proposed casings; indicate mudding jobs, coment ing points, and all other important proposed weight) On May 2, 1956, this well was perforated with two jet shots per foot from 129 1250 to 1270 feet. On May 3, 1956, this well was sand-water fracked through the above perforations with 20,000 gallons water, 30,000 pounds sand. Formation broke at 2600 pounds, with 20,000 gallons water, 30,000 pounds and average injection rate 44 hours is per minutes. Preliminary test, 2684 MGF per day. I understand that this plan of work must receive approval in writing by the Geological Survey before on ations may be communiced. Company Signature West 100 pounds and average injection rate 44 hours is per minutes. Preliminary test, 2684 MGF per day.	NOTICE OF INTENTION TO ABANDON WELL.	
Well No. 74 is located 1450 ft. from Siline and 1850 ft. from Willine of sec. 29 SW/4 of Section 29 T-29-N R-12-W NMPM (A Sec. No.) (Twp.) R-12-W NMPM (County or Subdivision) (State or Territory) West Kutz-Pictured Cliffs San Juan New Mexico (State or Territory) The elevation of the derrick floor above sea level is 5358 ft. DETAILS OF WORK (State names of and expected depths to objective sands; show size, weights, and lengths of proposed casings; indicate mudding jobs, coment ing points, and all other important proposed weight) On May 2, 1956, this well was perforated with two jet shots per foot from 129 1250 to 1270 feet. On May 3, 1956, this well was sand-water fracked through the above perforations with 20,000 gallons water, 30,000 pounds sand. Formation broke at 2600 pounds, with 20,000 gallons water, 30,000 pounds and average injection rate 44 hours is per minutes. Preliminary test, 2684 MGF per day. I understand that this plan of work must receive approval in writing by the Geological Survey before on ations may be communiced. Company Signature West 100 pounds and average injection rate 44 hours is per minutes. Preliminary test, 2684 MGF per day.		TUDE OF PEROPT NOTICE OF OTHER DATA)
Well No	(INDICATE ABOVE BY CHECK MARK NA	TORE OF REPORT, NOTICE, ON OTHER EXTEN
SW/L of Section 29 T-29-N R-12-W NMPM (Meridian) West Kutz-Pictured Cliffs San Juan (County or Subdivision) The elevation of the derrick floor above sea level is 5358 ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement ing points, and all other important proposed work) On May 2, 1956, this well was perforated with two jet shots per foot from 120 1250 to 1270 feet. On May 3, 1956, this well was sand-water fracked through the above perforations with 20,000 gallons water, 30,000 pounds sand. Formation broke at 2600 pounds, Treating pressure was 1100 pounds and average injection rate 44 by 15 per minutes. Preliminary test, 2684 MCF per day. I understand that this plan of work must receive approval in writing by the Geological Survey before on ations may be common ced. Company STAINING CH 2 CAS COMPANY Address 1 0 10 10 10 10 10 10 10 10 10 10 10 10	Well No. 74 is located 1450 ft. from	Farmington, New Mexico May 10 , 1956
West Kutz-Pictured Cliffs San Juan (County of Subdivision) The elevation of the derrick floor above sea level is		
The elevation of the derrick floor above sea level is	(½ Sec. and Sec. No.) (Twp.) (R	New Merico
The elevation of the derrick floor above sea level is	West Kutz-Pictured Cliffs San Just (County or 8	ubdivision) (State or Territory)
On May 2, 1956, this well was perforated with two jet shots per foot from 1250 to 1270 feet. On May 3, 1956, this well was sand-water fracked through the above perforations with 20,000 gallons water, 30,000 pounds sand. Formation broke at 2600 pounds. Treating pressure was 1100 pounds and average injection rate 44 barnls per minutes. Preliminary test, 2684 MCF per day. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be communicated. Company STATISTICS COMPANY Address 1.0.000 KEW MCF 10 PANY By By By	,	
On May 2, 1956, this well was perforated with two jet shots per foot from 1250 to 1270 feet. On May 3, 1956, this well was sand-water fracked through the above perforations with 20,000 gallons water, 30,000 pounds sand. Formation broke at 2600 pounds. Treating pressure was 1100 pounds and average injection rate 44 barnls per minutes. Preliminary test, 2684 MCF per day. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be communicated. Company STATISTICS COMPANY Address 1.0.000 KEW MCF 10 PANY By By By	DETAIL	S OF WORK
On May 2, 1956, this well was perforated with two jet shots per foot from 120 1250 to 1270 feet. On May 3, 1956, this well was sand-water fracked through the above perforations with 20,000 gallons water, 30,000 pounds sand. Formation broke at 2600 pounds with 20,000 gallons water, 30,000 pounds and average injection rate 44 barnla per minutes. Preliminary test, 2684 MCF per day. JUN 22 356 OR CON. COM. Lunderstand that this plan of work must receive approval in writing by the Geological Survey before objections may be commerced. Company Similar CH 2 CAS COMPANY Address 1.0. DAY 487	and the state of t	weights, and lengths of proposed casings; indicate mudding jobs, cement-
On May 3, 1956, this well was sand-water fracked through the above perforations with 20,000 gallons water, 30,000 pounds sand. Formation broke at 2600 pounds. Treating pressure was 1100 pounds and average injection rate 44 barnals per minutes. Preliminary test, 2684 MCF per day. JUN 22 1356 CM CON. COM. DIST. 3 LIUNGER AND CHARLES COMPANY Address P. C. AND 467 Address P. C. AND 467 D. D	(State names of and expected depths to objective saids, show sizes ing points, and all oth	er important proposed work)
with 20,000 gallons water, 30,000 pounds and. Formation broke at 2000 pounds. Treating pressure was 1100 pounds and average injection rate 44 beams a per minutes. Preliminary test, 2684 MCF per day. JUN 22 1356 OR CON. COM. DIST. 3 Lunderstand that this plan of work must receive approval in writing by the Geological Survey before op ations may be communed. Company STATION NEW MEMORY. Address D.	On May 2, 1956, this well was perform 120 1250 to 1270 feet.	ted with two jet shots per foot from
Company STATE CIL & CAS COMPANY Address P. C. LOW 487 TARMINGTON NEW MENTON D W By Jo. grant	with 20,000 gallons water, 30,000 pour Treating pressure was 1100 pounds and minutes. Preliminary test, 2684 MCF	average injection rate 44 harmls per per day. JUN 22 1356 OR CON. COM. DIST. 3
Address P. C. WA 487 TARMINGTON NEW MENTON D W By 20.900000000000000000000000000000000000	I understand that this plan of work must receive approval in w	writing by the Geological Survey before opportions may be commerced.
Address P. C. WA 487 TARMINGTON NEW MENTON D W By 20.900000000000000000000000000000000000	Company STATISTICS CH & CIS COM	PANY
	h 6 107 /07	
	FARMINITON NEW MEDICAL	10 By 10, 90em, -
		(u) \\\