
Form 9-831 a (Feb. 1951)



NOTICE OF INTENTION TO DRILL.

NOTICE OF INTENTION TO CHANGE PLANS....

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office
Lease No
Unit

SUNDRY NOTICES AND REPORTS ON WELLS

SUBSEQUENT REPORT OF WATER SHUT-OFF

SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....

NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING.	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	DOU'S I
NOTICE OF INTENTION TO ABANDON WELL		
(4)		
(INDICATE ABOVE BY CHECK MARK NAT	TURE OF REPORT, NOTICE, OR OTHER DATA)	
	Harch 18	, 1960
MA Alona E. Caller	(A.1).	
ell No is located ft. from	S line and S line of	***
	S)	sec,
12/4 (pf. finekien 95 1858 145	entere	
(5) 200, 22 200, 200,	(Meridian)	W/X/A
letak Gallan		KUI IVTN
(county or Sub	bdivision) (State of Tel riory)	
ne elevation of the derrick floor above sea level i	is allow to	₩3n
of the defiler hoof above sea level i	18 - 16 T. T.	1960
DETAILS	OF WORK	CON.
DEIAILS	OF WORK	
ate names of and expected depths to objective sands; show sizes, we ing points, and all other in winds to report the running of greats	eights, and lengths of proposed casings; indicate maddi important proposed work)	ng jobe, cément-
to names of and expected depths to objective sands; show sizes, we ing points, and all other ing points, and ing points in poi	eights, and lengths of proposed casings; indicate middle important proposed work) setten enging as fellows; setten and must to 6362'. 15 \$736\$ enging out at 6360', with used \$11670 1710').	The second section of the section of the second section of the section of the second section of the secti
to names of and expected depths to objective sands; show sizes, we imposite, and all other ing points, and it is a point of the points of	eights, and lengths of proposed casings; indicate middle important proposed work) sotion coming as follows; pale and must to 6368'. 15 First coming not at 6360', with used Gliffe 1710'). 50-50 Fermix '8" commut. Week	The second section of the section of the second section of the section of the second section of the secti
to names of and expected depths to objective sands; show sizes, we imposite, and all other ing points, and ing points, and ing points, and ing points in the points of the points	eights, and lengths of proposed casings; indicate middle important proposed work) setion enging as fallows; pale and must to 6962'. 15 STAC enging set at 6360', with must Gliffe 1710'). 96-90 Fermix "8" commut. NOC harded top stage with 50 am 50-5	The same of the sa
to names of and expected depths to objective sands; show sizes, we ing points, and all other ing points, and ing points, and ing points in a line of product in the points in the po	eights, and lengths of proposed casings; indicate middle important proposed work) setten enging as follows; rels and must to 6362'. 15 \$255 enging out at 6360', with well Gliffs 1710'). 90-90 Person "5" commit. Well imposed top stage with 90 as 90-51/59.	th coment etc have & opens 10 Posmix "B"
to names of and expected depths to objective sands; show sizes, we impoints, and all other in points, and all other in the same of professions of the same of professions of the same of t	eights, and lengths of proposed casings; indicate middle important proposed work) setten enging as follows; rels and must to 6362'. 15 \$255 enging out at 6360', with well Gliffs 1710'). 90-90 Person "5" commit. Well imposed top stage with 90 as 90-51/59.	The second section of the section of the second section of the section of the second section of the secti
to names of and expected depths to objective sands; show sizes, we impoints, and all other ing points, and all other ing points and all other ing and all other ing of the ing	eights, and lengths of proposed casings; indicate middle important proposed work) sotion enging as follows; tale and mid to 6962'. 15 5786 enging set et 6960', vit wed Gliffe 1710'). 50-90 Femals '8" enumet. Wet in the set of the stage with 90 as 90-91/59. If and drilled out casest stage	th conest pto here & apon 10 Posniz "3"
to names of and expected depths to objective sands; show sizes, we impoints, and all other ing points, and all other ing points and all other ing and all other ing of the ing	eights, and lengths of proposed casings; indicate middle important proposed work) setten enging as follows; rels and must to 6362'. 15 \$255 enging out at 6360', with well Gliffs 1710'). 90-90 Person "5" commit. Well imposed top stage with 90 as 90-51/59.	th conest pto here & apon 10 Posniz "3"
to names of and expected depths to objective sands; show sizes, we impoints, and all other ing points, and all other ing points and all other ing and all other ing of the ing	eights, and lengths of proposed casings; indicate middle important proposed work) sotion enging as follows; tale and mid to 6962'. 15 5786 enging set et 6960', vit wed Gliffe 1710'). 50-90 Femals '8" enumet. Wet in the set of the stage with 90 as 90-91/59. If and drilled out casest stage	th conest pto here & apon 10 Posniz "3"
to names of and expected depths to objective sands; show sizes, we impoints, and all other ing points, and all other ing points and all other ing and all other ing of the ing	eights, and lengths of proposed casings; indicate middle important proposed work) sotion enging as follows; tale and mid to 6962'. 15 5786 enging set et 6960', vit wed Gliffe 1710'). 50-90 Femals '8" enumet. Wet in the set of the stage with 90 as 90-91/59. If and drilled out casest stage	th conest pto hre & epon 10 Posniz "B'
to names of and expected depths to objective sands; show sizes, we imposite, and all other imposite to a solid and	eights, and lengths of proposed casings; indicate middle important proposed work) setion enging as fellows; pale and must to 6962'. 15 STAC enging set at 6960', with must Gliffe 1710'). 96-90 Fermix '8" commut. Wet is musted top stage with 90 ax 90-1/59. If and drilled out commut stage.	th coment pto here & apond 10 Posnix "b" cellar with
the names of and expected depths to objective sands; show sizes, we imposite, and all other imposite i	eights, and lengths of proposed casings; indicate middle important proposed work) setion enging as fellows; pale and must to 6962'. 15 STAC enging set at 6960', with must Gliffe 1710'). 96-90 Fermix '8" commut. Wet is musted top stage with 90 ax 90-1/59. If and drilled out commut stage.	th conent pto here & epone 10 Posnix "B' celler with
the names of and expected depths to objective sands; show sizes, we impoints, and all other ing points, and all other ing points of 3/4" hale with retery to called not at 1510" (hade of Fictor called not better stage with 300 or cannot stage cellar at 1510". Comments stage cellar at	eights, and lengths of proposed casings; indicate middle important proposed work) setion enging as fellows; pale and must to 6962'. 15 STAC enging set at 6960', with must Gliffe 1710'). 96-90 Fermix '8" commut. Wet is musted top stage with 90 ax 90-1/59. If and drilled out commut stage.	th conent pto here & epone 10 Posnix "B' celler with
the names of and expected depths to objective sands; show sizes, we impoints, and all other ing points, and all other ing points of 3/4" hale with reduce to the well of and 236 5-3 collar not at 1510" (hade of Pictus Committed bettern stage with 300 or commit stage collar at 1510". Committed bettern stage with 300 or committed bettern stage with 300 or committed bettern stage with 300 or committed bettern stage at 1510 or collar stage at 1510 or coll	eights, and lengths of proposed casings; indicate middle important proposed work) setion enging as fellows; pale and must to 6962'. 15 STAC enging set at 6960', with must Gliffe 1710'). 96-90 Fermix '8" commut. Wet is musted top stage with 90 ax 90-1/59. If and drilled out commut stage.	th coment sta have & epone 10 Pounts "B" cellar with
the names of and expected depths to objective sands; show sizes, we impoints, and all other ing points, and all other ing points of 3/4" hale with reduce to the well of and 236 5-3 collar not at 1510" (hade of Pictus Committed bettern stage with 300 or commit stage collar at 1510". Committed bettern stage with 300 or committed bettern stage with 300 or committed bettern stage with 300 or committed bettern stage at 1510 or collar stage at 1510 or coll	eights, and lengths of proposed casings; indicate middle important proposed work) setion enoing as fellows; rels and must to 6362'. 15 State enoing set et 6360', with used Gliffe 1710'). 90-90 Pennix "8" commit. Wet is musted top stage with 90 am 90-9 190 pai for 30 minutes. 190 pai for 30 minutes.	th compat sta have & especial 10 Posmix "B" celler with
the names of and expected depths to objective sands; show sizes, we imposite, and all other ing points, and all other ing points of 3/4" hale with reduce to the with reduce the sand at 1610" (hade of Pictus Committed bettern stage with 300 or commit stage cellar at 1610". Committed bettern stage with 300 or committed bettern stage cellar at 1610". Committed bettern stage cellar at 1610". Committed bettern stage at 1610 or committed at 1610 or comm	eights, and lengths of proposed casings; indicate middle important proposed work) setion enoing as fellows; rels and must to 6362'. 15 State enoing set et 6360', with used Gliffe 1710'). 90-90 Pennix "8" commit. Wet is musted top stage with 90 am 90-9 190 pai for 30 minutes. 190 pai for 30 minutes.	th compat sta have & especial 10 Posmix "B" celler with
the names of and expected depths to objective sands; show sizes, we imposite, and all other ing points, and all other ing points of 3/4" hale with reduce to the with reduce the sand at 1610" (hade of Pictus Committed bettern stage with 300 or commit stage cellar at 1610". Committed bettern stage with 300 or committed bettern stage cellar at 1610". Committed bettern stage cellar at 1610". Committed bettern stage at 1610 or committed at 1610 or comm	eights, and lengths of proposed casings; indicate middle important proposed work) setion enging as fellows; pale and must to 6962'. 15 STAC enging set at 6960', with must Gliffe 1710'). 96-90 Fermix '8" commut. Wet is musted top stage with 90 ax 90-1/59. If and drilled out commut stage.	th compat sta have & epone 10 Posmix "B" celler with
to names of and expected depths to objective sands; show sizes, we impoints, and all other ing points, and all other ing points of 3/4" hale with reducey to sand \$367' of 7" 60 205 and \$36' 5-5 outlier not at 1510' (bace of Fictor commits them collar at 1510'. Commits stage collar at 1510'.	eights, and lengths of proposed casings; indicate middle important proposed work) setion enoing as fellows; rels and must to 6362'. 15 State enoing set et 6360', with used Gliffe 1710'). 90-90 Pennix "8" commit. Wet is musted top stage with 90 am 90-9 190 pai for 30 minutes. 190 pai for 30 minutes.	th compat sta have & epone 10 Possiz "B" celler with

