## NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

	_		0:1	۰۰						6-23	Well	•
Operator_ Location		enne	CO U11	compan	iy		Le	ase_		Callow	No•	9
of Well:	Unit	ŧΙ	Sec.	28 T	WD.	29	Rge	•	13	County	San Juan	
· · · · · · · · · · · · · · · · · · ·		<u> </u>			<u></u>	Type	of Prod.	`	Method	County of Prod.	Prod. Med	ium
	<u> </u>	Vame	of Rese	rvoir	or Pool	<u>(0il</u>	or Gas)	<u>(</u> F	Flow or	Art. Lift)	(Tbg. or C	sg.)
Upper Completion	<u>n</u>		Gallup		·		T.A					
Lower			Daliata				0		-1			i
Completion Dakota					PRE-I	T.OW SH	Gas UT-IN PRE	SSUE	Elo RE DATA	)W	Tubing	<u> </u>
Upper Hou	r, da	ate	4/23/8	4	Length	of			SI pre	SS.	Stabilized	3
Compl S	hut-i	in	10:00 a	.m.	time shu	ıt-in 72	2 hours		psig	70	(Yes or No	
Compl Shut-in 10:00 a.m. Lower Hour, date 4/23/84 Compl Shut-in 10:00 a.m.			4	Length of time shut-in 72 hours				SI pre	SS.	Stabilized	. 1	
Compli S	nut-	ın '	0.00 a.i		time sn	rio	W TEST NO	<del>-</del> -	psig	021	(Yes or No	) no
Conmenced	at.	hou	r. date	*	4/26/84					roducing (Uppe	r or Lower)	ilauau
Time			sed time		47.207.04 Pres	ssure	1.111.	Proc	i. Zone	,,,,		TOWER
(hour, dat	te)	s	ince*	Uppe	r Compl.	Lower	Compl.	Ten	mp.	Rem	arks	
4/27/84 10:00 a.	m.	2	4 hours		70	20	15		<del></del>		<del></del>	
4/28/84 10:00 a.	m	Λ.	8 hours		70	20	20					-
10.00 a.	111.		o Hours				,,,					
								<del></del>				
				+	·.· · · · · · · · · · · · · · · · · · ·							
					<del></del>							
İ												
Production	n rat	e di	uring te	st.		1				<u>!</u>		
Oil:		JO 4.	BOPD b	ased	on	В	bls. in_		Hr	sGra	.vGOF	·
Gas:		4	01	MCFPD	; Tested	thru (	Orifice o	r Me	eter):_	sGra Meter		
F							UT-IN PRE				Stabilized	12
Upper Hour, date Compl Shut-in					Length of time shut-in			SI press.  osig			(Yes or No)	
	ower Hour, date				Length of			SI press.			Stabilized?	
Compl Si	<u>านใ – i</u>	<u>in</u>	,		time shu	ut-in	<del> </del>		psig		(Yes or No	)
5	a b /	<u> </u>	4.4.5	W.W.		FLO	W TEST NO			moducing (Unne	or Lower	
Time	at (	t (hour, date)**			Pressure			Zone producing (Upper Prod. Zone			1 of Bower	· · · · · · · · · · · · · · · · · · ·
(hour, dat	ce)	si	nce **		r Compl.				emp.	Rem	arks	
				<del>                                     </del>							1.69 St. 20	
										REWEM		
				<del> </del>					<u> </u>	JAN 1 8 19	<b>U</b>	
						<u> </u>	i					
				İ						OIL CON.	DIV.	
<u> </u>				+	·	<del>                                     </del>				DIST. 3		
Production	n rat	e d	uring te	st								
Oil:			BOPD b	ased	on	B	bls. in	`	Hrs.	Grav	GOR	<del></del>
Gas:			- <del></del>	_MCFP	D; Teste	i thru	(Urilice	or r	meter):	<u></u>	<del></del>	-
REMARKS:_			····	<del></del>		<del></del>						··········
								~				
I hereby knowledge		Lfy	that the	info	rmation	horein				nd complete to		of my
_	,	JAN	N 181	985	_		Operato	<u>r_)</u>	Tennec	o Oil Company		
Approved:					19	_	p. 6/	To h	-111:00	Perision .	Kathari	ne Jenkin
New Mexic						11				Julian		JUINT
By			by CHARLE				Title /		AGent	/ 		<del></del>
Title						_	Date	]	Decembe	r 31, 1984		·

## MORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven may after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Commission.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Commission in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-bead pressure in each has stabilized, provided
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: If, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

- 7. Pressures for gas-mone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 2-hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of-each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test
- 24-bour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges, the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressure as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Astec District Office of the New Mexico Oil Conservation Commission on Northwest New Mexico Packer Leakage Test Form Revised 11-1-58, with all desadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only). A pressure versus time curve for each zone of each test shall be constructed on the reverse side of the Packer Leakage Test Form with all deadweight pressure points taken indicated thereon. For oil zones, the pressure curve should also indicate all key pressure changes which may be reflected by the recording gauge charts. These key pressure changes should also be tabulated on the front of the Packer Leakage Test Form

