

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE
(Other instructions on reverse side)

Docket Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

SF-080224

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT ABBREVIATION NAME

Gallegos Canyon Unit Com D

8. FARM OR LEASE NAME

9. WELL NO.

160

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC., T., R., M., OR ALK. AND
SURVEY OR AREA

NE/SE Sec. 27, T29N, R12W

12. COUNTY OR PARISH 13. STATE

San Juan

NM

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Amoco Production Company

3. ADDRESS OF OPERATOR

2325 E. 30th, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface

1850' FSL x 1190' FEL

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

14. PERMIT NO.

15. ELEVATIONS (Show whether DT, ST, GA, ETC.)

5384' RDB

6. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PLUG OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in and rigged up service unit on 8-5-85. Tripped in and set a drillable bridgeplug at 5836'. Pressure tested casing to 1000 psi for 30 minutes. Milled up bridgeplug with nitrogen foam. Cleaned out sand fill with nitrogen foam. Landed 2-3/8" tubing at 5991' and released the rig on 8-13-85.

I hereby certify that the foregoing is true and correct

SIGNED

BS Shaw

TITLE Adm. Supervisor

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE JUL 25 1986

FARMINGTON RESOURCE AREA

BY

Smm

*See Instructions on Reverse Side

NMOCC