

Sec-30	
T29N-R17W	
.	

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency Window Rock, Ariz.

Navajo


Allottee Navajo Tract #20

Lease No. 14-20-603-5024

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<u>Subsequent report for setting 5" liner, squeezing and testing</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)



October 4, 1963

Well No. 2 is located 1980' ft. from S line and 660' ft. from W line of sec. 30

MM/SM-Sec-30
(1/4 Sec. and Sec. No.)

29N
(Twp.)

R17W
(Range)

MMPM
(Meridian)

Pajarito Area
(Field)

San Juan

(County or Subdivision)

New Mexico
(State or Territory)

RECEIVED

OCT 7 1963

The elevation of the derrick floor above sea level is 5240' ft.

DETAILS OF WORK

U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

- 9-23-63 - 7195' Present TD: Ran and Set 5" OD liner in well, Bottom of liner at 7194', Top of liner at 6122', Top of liner hanger at 6117', Cased. W/75 Sax 50/50 Perm. Cnt. Pumped plug to 7160' W/800# Press., (W/Brown oil Tool shoe on bottom and Float Collar @ 7160')
- 9-24-63 - WOC - Pressured casing W/700# on top of liner and formation took fluid. Ran Hallib. RTTS Tool, Set at 6027' in 7" Casing, Squeezed top of liner with 75 Sax Reg. Cement, had standing pressure of 1000#, left 27' on top of liner. WOC and pressured up 7" Casing W/2000# and Liner Held Ok.
- 9-28-63 - Drilled liner shoe and formation to 7227', ran tubing and set packer at 6146' and snubbed formation from 7195' to 7227' for 8 hrs. (Mud was displaced in tubing with water) Snubbed tbg. down from (500'-6500') W/Fluid level at 6000' snubbed all fresh water, no trace of oil, gas or salt water.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Amerada Petroleum Corporation

Address Box 1469

Durango, Colorado

By L.A. Pettyjohn

Title District Field Clerk