

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240
DISTRICT II
P.O. Drawer DD, Artesia, NM 88210
DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O.Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	3004507873
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	7. Lease Name or Unit Agreement Name Sanchez Gas Com B
2. Name of Operator AMOCO PRODUCTION COMPANY Attention Pat Archuleta	8. Well No. #1
P.O. Box 800 Denver Colorado 80201 303-830-5217	9. Pool name or Wildcat Basin Dakota
4. Well Location Unit Letter G : 1650 Feet From The NORTH Line and 2100 Feet From The EAST Line Section 28 Township 29N Range 10W NMPM SAN JUAN County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	

11. Check Appropriate Box to Indicate Nature of Notice Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MIRUSU 3/18/97.

Set CIBP at 3722', load and test csg to 500#. Held okay. Ran CBL to determine toc at 920'.

Spot cement plug inside csg from 3722'-3300' w/ 32 sxs CI-B cement. Shoot sq z holes at 1517', could pump into holes. TIH spot sement plug from 1723'-1300', inside csg w/33 sxs CI-B cement.

Spot cement plug inside csg from 879' to surface w/85 sxs CI-B cement.

Cut off wellhead, top off csg, install marker.

RDMOSU 3/20/97.

RECEIVED
APR - 7 1997

OIL CON. DIV.
DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE _____ TITLE Staff Assistant DATE 04-03-1997
TYPE OR PRINT NAME Pat Archuleta TELEPHONE NO. 303-830-5217

(This space for State

APPROVED BY _____ TITLE Deputy Oil & Gas Inspector DATE 5-6-97

CONDITIONS OF APPROVAL, IF ANY: