COMP

OIL COM. DIV.

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

Location of Well: B252911 Page 1

OIL CONSERVATION DIVISION NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator: AMOCO PRODUCTION COMPANY Lease/Well #: EATON A 001E CMGLD RTU:0-000-00 County: SAN JUAN Meter #:02907 MEDIUM PROD TYPE PROD METHOD PROD NAME RESERVOIR OR POOL UPR TBB COMP Flow aton A1E. 02907 Ex 605 LWR PRE-FIOW CHITT-TH DEFECTIVE 736 Flow COMP Length of Time Shut-In SI Press. PSIG Stabilzed Hour/Date Shut-In 72 Hours 02/13/92 UPR COMP 10:40 AM 72 Hours 01/13/92 LWR COMP 10:40 AM FLOW TEST DATE NO.1 Zone Producing (Upr/Lwr) Commenced at (hour, date) * PRESSURE Prod LAPSED TIME TIME Temp. REMARKS Lower SINCE* Upper (hour, date) TUS 207 Both Zones SI 02/13/92 Day 1 318 cos 208 Both Zones SI 01/14/92 Day 2 TUB 408 552 Cas 408 Tub 410 Both Zones SI 02/15/92 Day 554 Cas 410 Day 01/16/92 556 Tub 414 01/17/92 Day 198 TJB 428 01/18/92 Day 195 Tub 430 Production rate during test BOPD based on ____ BBLs in ____ Hrs ___ Grav GOR ___ Oil: MFCPD: Tested theu (Orifice or Meter): METER Gas: MID-TEST SHUT-IN PRESSURE DATA SI Press. PSIG Length of Time SI Hour, Date SI UPR COMP MART 0 1992 LWR

(Continue on reverse side)

FLOW TEST NO. 2

Zone producing (Upper or Lower):

TIME (hour, date)	LAPSED TIME SINCE ##	PRESSURE		PROD. ZONE	
		Upper Completion	Lower Completion	TEMP.	REMARKS
					•
	L	!	<u> </u>	<u> </u>	
Production rate d	uring test				
Oil.	BOD	D based on	Dhia :-		Grav GOR
G25:		MCF	PD: Tested thru	(Orifice or Meter):
Pemarke:					
Kemars.					
					
1 haasha aanifa d	haa aha :-£a:	bii-	.13		
і петеру септу и	iat the informati	on nerein contain	ed is true and co	implete to the bes	st of my knowledge.
Approved	MAK IV	736	19 (Operator	Imoco Froduction
New Mexico O	il Conservation I	Division			Inoco Production
(Isiai na	d Signat by CLIAO	ine e tters is	1		2 2
By				Title	reld Jech
Title	ME & GAS INSPE	CTOR, DIST. #3	•	Date3	- 9-92
TRIC			I	Date	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

 A packer leakage user shall be commenced on each multiply completed well within seven days after actualcompletion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Commenced at (hour, date) **

- 2. At least 72 hours gains to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure subilization. Both zones shall remain shut-in until the well-head pressure in each has subilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test Nin.1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following complains of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).