

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT---" for such proposals.

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.
SF- 080000-A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Simmons E-1

9. API Well No.

300450791200

10. Field and Pool, or Exploratory Area

Blanco Mesa Verde

11. County or Parish, State

San Juan County, NM

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil ☒ Gas ☐ Other

2. Name of Operator

D.J. Simmons Company

3. Address and Telephone No.

(505)326-3753

3005 Northridge Drive, Suite L Farmington, NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Surface: 790 FNL x 1550 FEL Sec 26 T29N R9W

Bottom Hole: 1535 FNL x 1941 FEL Sec 26

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☒ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations. Fully state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depth for all markers and zones pertinent to this work.)*

09/23-09/24/95

Section Mill Window from 3800' to 3850'. Set 25 sk kick off plug with top @ 3827'.

09/25-10/03/95

P.U. Directional drlg tools. Drill 6 1/8 side track hole to 5250' measured depth. Directional surveys from Baker Hughes Inteq. Bottom hole location 5250' measured depth 4964.75' true vertical depth. 745.46' South and 391.21' West of the surface location. BHL: 1535 FNL x 1941 FEL Sec. 26, T29N, R9W.

10/04/95

Ran 4 1/2", 11.6 ppF, J-55 casing. Shoe at 5250' (m.d.) cement first stage with 225 sks class "b". Open stage collar. Attempt to circ out excess cmt. Lost circulation. Set slips. N.D. BOPE. N.U. well head. Release Rig.

10/10/95

MIRU. Big A 26. P.U. 2 3/8" tbg. Clean out 4 1/2" csg to PBTD of 5208'.

10/12/95

Ran CBL. Top of cmt behind 4 1/2" csg @ 4910' (m.d.). Perforate two holes @ 4820'. Set cmt retainer @ 4778'. Squeeze 4 1/2" annulus with 75 sks class "b".

10/13/95

Drill out retainer. Ran CBL. Top of cmt @ 4540'. Perforate two holes @ 4485'.

10/14/95

Squeeze 4 1/2" with 100 sks class "b" under retainer..

10/15/95

Drill out retainer. Ran CBL. Cmt top @ 3960'. Perforate two holes @ 3940'.

10/16/95

Set cmt retainer @ 3896'. Squeeze 4 1/2 annulus with 50 sks class "b".

10/17/95

Drill out retainer. Ran CBL. Cmt top @ 3668'. Clean out to 5214'. Release Rig.

14. I hereby certify that the foregoing is true and correct

Signed

Title Operations Engineer

Date

ACCEPTED FOR RECORD
JAN 22 1996

(This space for Federal or State office use)

Approved by

Title

Date

JAN 22 1996

Conditions of approval, if any:

AMOC

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

FARMINGTON DISTRICT OFFICE

BY 220

*See Instruction on Reverse Side