


(SUBMIT IN TRIPLICATE)

Indian Agency Navajo

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allottee _____

Lease No. 14-00-003-2100



SUNDRY NOTICES AND REPORTS ON WELLS

| | |
|---|--|
| NOTICE OF INTENTION TO DRILL | SUBSEQUENT REPORT OF WATER SHUT-OFF |
| NOTICE OF INTENTION TO CHANGE PLANS | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | SUBSEQUENT REPORT OF ALTERING CASING |
| NOTICE OF INTENTION TO REDRILL OR REPAIR WELL | SUBSEQUENT REPORT OF REDRILLING OR REPAIR |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | SUBSEQUENT REPORT OF ABANDONMENT |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | SUPPLEMENTARY WELL HISTORY |
| NOTICE OF INTENTION TO ABANDON WELL | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 28, 19 61

Well No. 3 is located 640 ft. from N line and 640 ft. from W line of Sec. 30
0 1/4 Sec. 30 29N 14W 187N
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wilcox San Juan New Mexico
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5445.7 6.1.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Intend to plug hole as follows:

4750-4800 - Cement plug w/ 16 sacks cement

1400-1500 - ditto

1325-1425 - ditto

900-1000 - ditto

Fill hole with mud and get 15' cement plug to surface with approx. 16 sacks cement. Break dry hole surface.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company The British-American Oil Producing Company

Address P. O. Box 130

Farmington, N.M.

By San J. Stone

Title Field Superintendent

RECEIVED
MAR 1 1945
OFFICE OF THE
DIRECTOR

RECEIVED

RECEIVED
MAR 1 1945
OFFICE OF THE
DIRECTOR

RECEIVED
MAR 1 1945
OFFICE OF THE
DIRECTOR

RECEIVED
MAR 1 1945
OFFICE OF THE
DIRECTOR