Form 9-831 (April 1952)	ŧ
(Aprii 1952)	

*		
	4	
	•	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Agency
B
Allettee
Lease No. 14-20-603-9100

NOTICE OF WEIGHT		
NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFE GO F 1 1
NOTICE OF INTENTION TO CHANGE PL	ANS	SUBSEQUENT REPORT OF SHOOTING OR ACTUALING
NOTICE OF INTENTION TO TEST WATER	R SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OF	REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR		SUBSEQUENT REPORT OF ABANDONMENT.
NOTICE OF INTENTION TO PULL OR AL		SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON W	/ELL	U. S. GEOLOGIA, NEW ME
(INDICATE	ABOVE BY CHECK MARK NAT	URE OF REPORT, NOTICE, OR OTHER DATA)
Hereje *B* Vell No is loca	440 to to	[N] 1:
eli 140, 15 loca	itedit. from	line and to ft. from w line of sec.
(14 Sec. and Sec. No.)	(Twp.) (R	ange) (Meridian)
VI. Lident	San Jaca	Northean
(Field)	(County or St	ubdivision) (State or Territory)
militari da Un Ameni	D4 #1#	
#11146 to TD 4790'. #10'. 1005 recevery. 4750-4750.5 - 44 4850.5 - 4410 -	Rigged up 5j.º os Avg. core time ght engaler glac black luminated	tro berrel and act Goes #1 from 4790 to 15.9 min./ft. Description as follows: Mechite sand stone v/ edl show shale with no shore.
#111e4 to TD 4790'. #111e4 to TD 4790'. #10'. 1005 recevery. 4750-4750.5 - 41 4850.5 - 4610 -	Rigged up 5j.º en 1vg. core time ght engaler glas black laminated TIME RES	se berrel and out Goes #1 from 4790 to 15.9 min./ft. Description as follows: Mecalte sand stone v/ edl show shale with me show.
villet to TD 4790'. ? #10'. 100\$ recevery. 4790-4790.5 - 44 4890.5 - 4410 - ?	Rigged up 5½° en Avg. core time ght engaler glas black laminated	se herrel and out Goes Al from 4790 to 15.9 min./ft. Description as follows Machite cand stone w oil show shale with no show.
#11144 to TD 4790'. #10'. 160\$ recovery. 4790-4790.5 - ti. 4890.5 - 4610 -	Rigged up 5jr ee Avg. eere time ght engaler glas black lamineted TIME IME	see bessel and out Goes #1 from 4790 to 15.9 min./ft. Description as follows Maccite and stone v/ oil abov shale with no show. FEB 2 7 1991 OIL (2)
#111e4 to TD 4790'. #10'. 1606 secrety. 4750-4750.5 - 44 4850.5 - 4610 -	Rigged up 5% on Avg. core than the complex glass black laminated	se harrel and out Gore Al from 4790 to 1549 min./ft. Description as follows Mechite cand stone w oil show shale with no show. FEB 2 7 1951 Oil Gore
#11104 to TD 4790'. #16'. 1605 recovery. 4750-4750.5 - 44 4850.5 - 4610 - 1	Algori up 53° on Avg. core time stat engular glass black lamingted IREL ELE must receive approval in write stricen 011 Product	is barrel and out Goes Al from 4790 to 15.9 min./ft. Description as follows Mechite cand stone y oil show shale with no show. FEB 2 7 1951 Oil Commenced. Cing Company
#111e4 to TD 4790'. #30'. 1005 recevery. 4790-4790.5 - 44 4890.5 - 4610 -	orican Cil Produ	se harrel and out Gore Al from 4790 to 1549 min./ft. Description as follows Mechite cand stone w oil show shale with no show. FEB 2 7 1951 Oil Gore
#11104 to 7D 4790', 230', 1805 secretary, 4790-4790, 5 = 44 4890, 5 = 4610 = 1 4890, 5 = 46100, 5 = 46100, 5 = 46100, 5 = 46100, 5 = 46100, 5 = 46100, 5 = 46100, 5 = 46100, 5 = 46100, 5 = 46100, 5 = 46100, 5 = 46100, 5 = 46100, 5 = 46100, 5 = 46100, 5 = 46100, 5 = 461000, 5 = 461000, 5 = 461000, 5 = 461000, 5 = 461000, 5 = 461000, 5 = 461000, 5 = 461000, 5 = 4610000, 5 = 4610000, 5 = 4610000, 5 = 4610000, 5 = 4610000, 5 = 46100	orican Cil Produ	se harrel and out Gore Al from 4790 to 1549 min./ft. Description as follows Mechite cand stone w oil show shale with no show. FEB 2 7 1951 Oil Gore
#11104 to 7D 4790', #26', 2605 secretary, 4750-4750, 5 = 44, 4850, 5 = 4610 = 10 mpany The British-landompany The British-landompany	orican Cil Produ	se harrel and out Gore Al from 4790 to 1549 min./ft. Description as follows Mechite cand stone w oil show shale with no show. FEB 2 7 1951 Oil Gore

• • •