

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

RECEIVED  
AUG 7 1998

OIL CON. DIV.

1. Type of Well  
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

MOUNTAIN STATES PETROLEUM CORP.

3. Address and Telephone No.

P O BOX 3531, MIDLAND, TX 79702 915/685-0878

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FNL & 660' FEL Sec. 28, T29N, R14W, NMPM

5. Lease Designation and Serial No.

14-20-603-2168A

6. If Indian, Allottee or Tribe Name

Navajo Nation

7. If Unit or CA, Agreement Designation

NW Cha Cha Unit

8. Well Name and No.

NW Cha Cha Unit 36

9. API Well No.

30-045-07924

10. Field and Pool, or Exploratory Area

Cha Cha Gallup

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☒ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- 1) MI&RU pulling unit 5-8-97.
- 2) Set 35 sx cement plug 3887-3577' in 5-1/2" casing. Tagged cement at 3577'. Cement Class G Neat with slurry wt 15.6.
- 3) Set 20 sx cement plug 2701-2601' inside 5-1/2" casing. Cement Class G Neat with slurry wt 15.6.
- 4) Set 180 sx cement plug 1098-776' inside and outside 5-1/2" casing. Tagged cement at 612'. Cement Class G with 2% CaCl with slurry wt 15.6.
- 5) Set 100 sx cement plug 225-surface inside and outside 5-1/2" casing and 8-5/8" casing. Cement Class G Neat with slurry wt 15.6.

Installed dry hole marker. RD & MO. Location reclamation.

WELL PLUGGED AND ABANDONED 5-21-97. Approved as to plugging of the well and liability under bond is retained until surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed [Signature] Title Agent

(This space for Federal or State office use)

Date 5-22-97

Approved by [Signature] Conditions of approval, if any:

Title

Date

MAY 28 1997

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements, or representations as to any matter within its jurisdiction.

FARMINGTON COPY