

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
SUNDRY NOTICES AND REPORT ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT" - for such proposals.

FORM APPROVED
Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.
SF-078209

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Gallegos Canyon Unit #28

9. API Well No.

3004507931

10. Field and Pool, or Exploratory Area

N. Pinion Fruitland Sand

11. County or Parish, State

San Juan, New Mexico

1. Type of Well

☐

Oil
Well

☒

Gas
Well

☐

Other

2. Name of Operator

Amoco Production Company

Attention:

Patty Haeefe

3. Address and Telephone No.

P.O. Box 800, Denver, Colorado 80201

(303) 830-4988

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

400' FNL 770' FEL Section 30 T29N R12W Unit A

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐

Notice of Intent

☒

Subsequent Report

☐

Final Abandonment Notice

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Bradenhead Remediation

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or
Recompletion Report and Log Form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Amoco Production Company has performed a workover on this well per the following:

MIRUSU 6/17/96. Blow down well. ND WH. NU BOP. Set CIBP at 880', circulate hole clean, load and test casing to 500 psi, held ok. Run CBL from 880' to surface, TOC at 746'. Shoot squeeze holes at 700' with 2 shots, .340" diameter, 4" gun, 120 deg phasing. Pump dye water on perfs to circulate to surface out BH valve. Pump 250 sx Class B ^{lit} cement, 12.7 ppg, pump 50 sx tail in ^{Next} cement, circulate on BH 20 bbls cement. Tag cement at 610', drill out cement to 708', load and test squeeze to 500 psi, held ok. Drill out 5.5" ES plug from 880-882'. Hole is clean. BH pressure 0 psi. Re-land tubing. RDMOSU 6/21/96.

RECEIVED
JUL 23 1996
OIL CON. DIV.
BLM

RECEIVED
BLM
96 JUL 15 AM 9:02
070 FARMINGTON, NM

14. I hereby certify that the foregoing is true and correct

Signed

Patty Haeefe

Title

Staff Assistant

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

JUL 23 1996

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statement or representations as to any matter within its jurisdiction.