(April 1952)							
		X					
1		i					

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Agency
Allottee

SUNDRY NO		SUBSEQUENT REPORT OF	WATER SHUT-OFF	4-4-10
CE OF INTENTION TO DRILL	i 11	SUBSEQUENT REPORT OF	SHOOTING OR ACIDIZING	
CE OF INTENTION TO CHANGE PLANS		SURSEQUENT REPORT OF	ALTERING CASING	-seeration S
CE OF INTENTION TO TEST WATER SHU	I=UFF	SUBSEQUENT REPORT OF	REDRILLING OR REPAIR	LEGISTON OF WAY
CE OF INTENTION TO REDRILL OR REPA	NIK WELL	SUBSEQUENT REPORT OF	ABANDONMENT	
CE OF INTENTION TO SHOOT OR ACIDIZ	CASING	SUPPLEMENTARY WELL H	ISTORY	X
ICE OF INTENTION TO PULL OR ALTER	JADING	Handou Frac.		
ICE OF INTENTION TO ABANDON WELL.				
(INDICATE ABO)	E BY CHECK MARK NAT	URE OF REPORT, NOTICE, O	R OTHER DATA)	
			August 26	, 19 <b>.60</b>
Ojo Amarillo	330 ft. from	[N] line and <b>2810</b>	ft. from W line of	sec. 28
			impm	
4 NW/4 Section 28 ()4 Sec. and Sec. No.)	<b>474</b> 1		feridian)	<b>A</b>
(14 Sec. and Sec. 190.)	Sea		(State or Territor)	r)
(Field)	(County or 8	Subdivision)	(State or Textror)	•
te names of and expected depths to obje	DETAILS active sands; show sizes, ing points, and all oth 5195°. Clean	S OF WORK , weights, and lengths of pr er important proposed wo  Out Total Depth	K121'-5130' (Per	f. 4 sh./ft.
e elevation of the derrick floor to names of and expected depths to object past 15, 1960 Total Depth Sandell fractured Le with 41,888 Gale. L Maximum treating p Injection Rate: 40.1	DETAILS scrive sands; show sizes, ing points, and all oth 5195°. Clean rear Gallup per case Crude and	S OF WORK, weights, and lengths of prier important proposed wo in Out Total Depth represented interval.  40,000 Send.	S121'-5130' (Per Breakdown pressure- REFEVE	1. 4 sh./ft. ere1600 p -1975 psi.
past 15, 1960 Total Depth Sendell fractured Lowith 41, 888 Gale. L. Maximum treating p injection Rate: 40.1	DETAIL: sective sands; show sizes, ing points, and all oth 5195°. Clean reer Gallup per sease Crude and ressure4099 bbls./min. ?	S OF WORK , weights, and lengths of prier important proposed wo leave the company of the company of the company of the company	S121'-5130' (Per Breakdown pressure- REFEVE AUG-31 1 OIL CON. DIST.	1. 4 sh./ft. ure1600 p -1975 pai. 960 COM. 3
past 15, 1960 Total Depth Sandell fractured Lowith 41,888 Gale. L. Maximum treating p injection Rate: 40.1	DETAIL: sective sands; show sizes, ing points, and all oth 5195°. Clean reer Gallup per sease Crude and ressure4099 bbls./min. ?	S OF WORK , weights, and lengths of prier important proposed wo leave the company of the company of the company of the company	S121'-5130' (Per Breakdown pressure- REFEVE AUG 31 1 OIL CON. DIST.	1. 4 sh./ft. ure1600 p -1975 pai. 960 COM. 3

以"性"。程度多少的联系的数。

and the second of the second of the second

and the second of the second o

"连续"接触的数。一致,他从上,他们推荐人人更多为第二、"你"的。 (1) Long to the \$55.00 that the secretary supplies to all news or the secretaries are self-and the state of the following of the second displacement is a second to the second second second second second

अध्यक्ति क्षेत्र एक क्षेत्र कर केली । इसे अस्ट केली हैं

entre masser l'experiment de la companya de sancial contra en entre de la companya de sancial de la companya del companya del companya de la companya de la

TO COME BY: VAN E. DYNES

THE CONTRACTOR OF THE PARTY.