Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135				
Budget Bur	eau No.	1004-013	35	
Expires:				

5. Lease Designation and Serial No

6. If Indian, Allottee or Tribe Name

Change of Plans

**New Construction** 

Water Shut-Off

Non-Routine Fracturing

Conversion to Injection

NM-0	14	131	78

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Here "APPLICATION FOR REPORT " for each proposals."

Use "APPLICATION FO	OR PERMIT—" for such proposals		
SUBMI	7. If Unit or CA, Agreement Designation		
1. Type of Well  Oil  Well  Well  Other	8. Well Name and No.		
2. Name of Operator  Texaco Exploration & Production Inc.  3. Address and Telephone No.		H.J. Loe Federal B #3  9. API Well No.  30-045-07955	
3300 N. Butler, Farmington N.M. Location of Well (Footage, Sec., T., R., M., or Survey	10. Field and Pool, or Exploratory Area  Fulcher Kutz PC  11. County or Parish, State		
890' FSL & 790' FWL, Unit M Sec. 23-T29N-R12W		San Juan, NM	
2. CHECK APPROPRIATE BOX	(s) TO INDICATE NATURE OF NOTICE,	REPORT, OR OTHER DATA	
TYPE OF SURMISSION	TYPE OF	ACTION	

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Abandonment

Recompletion

Plugging Back

Casing Repair

Altering Casing

Texaco E. & P. Inc. has performed the following work:

Final Abandonment Notice

8/14/92. MIRUSU. Ran TDT from 1746'-1100'. Ran CBL from 1746'-700', TOC @ 1550'. Perfed 2 squeeze holes at 1510'. Spotted 4 bbls cement, couldn't get pressure. Pumped cement away. Spotted 8 bbls & started squeezing. Circ. up bradenhead. Set retainer @ 1431'. Cemented w/ 360 sks cement. Good returns. Drilled out retainer. Circ. out cement from 1606'-1706'. Tested to 1000#. Held. Perfed 4 JSPF from 1618'-1622'. Swabbed. Acidized perfs w/ 200 gals. 15% HCl. Fraced perfs w/ 8000 gals. gel and 35,175 lbs sand. Set RBP. Perfed @ 1520'-1550'w/ 4 JSPF. Acidized perfs w/ 1200 gals. HCl acid and 1700 lbs of rock salt. Fraced perfs w/ 30,000 gals. gel and 144,000 lbs sand. Clean out. TIH w/ production equipment. RDMOL.

14. I hereby certify that the foregoing is true and correct Signed	BS Title Area Manager	
(This space for Federal or State office use)  Approved by Conditions of approval, if any:	Title	ACCEPTED FOR RECORD
		NOV 18 1992
Title 18 U.S.C. Section 1001, makes it a crime for any p or representations as to any matter within its jurisdiction.	erson knowing y and willfully to make to any departme	ent or agency of the United Manies Talky falls Order Course April Mandulent statement

\*See Instruction on Reverse Side