NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122
Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

ool A	rtee	tured	Cliffe	Fo	rmation	Plotu	LONG COTTO	To	County_		Say	Just
nitial		<u> </u>	Annua	i.		Spe	cial		Date of	Test	12	19-57
mpany	PAN AM	RIGAN	PETRIL	FIN CO	ir.	Lease	Truji)	le Ges Vet	W e	ll No	1	
it _	K	Sec. 2	Twp		Rg	e 1	Pu:	rchaser_	l Pago Mai	ment G	no Con	
sing	Sès I	Wt	<u> </u>	D. 146	12" Se	t at	160 F	erf	<u> </u>	To	131	<u> </u>
bing_	L,46 T	Wt	3 1.	D	∆ Se	tat_	7781 I	Perf	MI	_To	_17	2
ıs Pay	: From	1764	_To	196	L 17	75	xG 0,69	-GL	1225	_Bar.Pr	ess	12
oduci:	ng Thru	Ca:	sing		Tul	oi.ng		Type Wongle-Brad	ell (100 - 3	ingle	
ate of	Complet	tion:_	11-41	-57	Packer	r	Si •	ingle-Brad Reserv	enhead-G. oir Temp.	G. or	G.O. I	oual
						OBSER	VED DATA	\				
sted '	Through	(Pro	ver) (C	hoke)	(Meter)	*			Туре Тар	os		
			Flow Da				Tubir	ng Data	Casing I			
(Prover) (Line)				Diff.	Temp.		Temp.			1	Duration of Flow
	Size	S:	ize	psi.g	h _w	$^{o}_{\mathrm{F}}$.	psig	°F.	psig	°F∙		Hr.
	1m 28		_				667		447		Ţ	
		1				· · · · · · · · · · · · · · · · · ·				 	-	
							_		<u> </u>	1		
٠.	Coeffici (24-Hou		√ h _w p		essure osia	Flow Fac			4 "	or	Q-MC @ 15.	0 25 psia
	-		•		*	*			•	•		<u> </u>
	· · · · · · · · · · · · · · · · · · ·									•		
vity o	id Hydro	id Hydı	rocarbo	ns _e ^{-§})		cf/bbl.	CALCUIAT • •	Spec: Spec:	ific Gravi ific Gravi	ity Flo		
	(psia)	Ρŧ	Fc	Q	(F _c Q) ²	(1	r _c () ² L-∈-s)	P _w 2	$P_c^2 - P_w^2$		al. P _w	Pw Pc
										1		
solute MPANY DRESS ENT ar	nd TITLE	AN AND		-	MI CORP	CEATION CALCO		15ano	<u> </u>	/Ŕ	Œ	VED
TNESSI MPANY										1 4	0 c///	1958
	***				مثك بعد		1ARKS			OIL	CON.	COM.
# FO	i mot i	rondq	ano to	03000	proximi	ay of e	eeupded	dwillings	le:		DIST.	•/

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure (P_W) . MCF/da. @ 15.025 psia and 600 F.
- Pc= 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- P_w Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- $h_{\mbox{\scriptsize W}}$ Differential meter pressure, inches water.
- Fg Gravity correction factor.
- Ft Flowing temperature correction factor.
- F_{pv} Supercompressability factor.
- n I Slope of back pressure curve.

Note: If $P_{\mathbf{W}}$ cannot be taken because of manner of completion or condition of well, then $P_{\mathbf{W}}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\mathbf{t}}$.

OIL CONSERVATION COMMISSION											
AZTEC DISTRICT OFFICE											
No. Copies Received 3											
DISTRIBUTION											
	NO.										
Operator											
Santa Fe											
Provation inter-		-									
State Lane (1888)	·	-									
U. S. 6. S.		-									
Transporter	1	1									
File											