

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised 1-1-89

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O.Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.

3004507985

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name

Pearce Gas Com

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

AMOCO PRODUCTION COMPANY

Attention

Pat Archuleta

8. Well No.

#1

P.O. Box 800 Denver Colorado 80201 303-830-5217

9. Pool name or Wildcat

Basin Dakota

4. Well Location

Unit Letter K : 1470 Feet From The SOUTH Line and 1775 Feet From The WEST Line

Section 23 Township 29N Range 11W NMPM SAN JUAN County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MIRUSU 3/10/97.

Csg collapsed at 4018', w/state decided to shoot off tbg at 5100' and squeeze DK perms from and cover GP also; pumped 100 sxs CI-B cement from 4690'-6090'. Tag toc at 4679' to cover the Dk and GP intervals.

Spot cmt plug inside csg from 3135'-3962' w/ 63 sxs CI-B cement.

Spot cmt plug inside csg from 2545'-2745' w/13 sxs CI-B cement.

Spot cmt plug inside csg from 1235'-1747' w/40 sxs CI-B cement.

Spot cmt plug from 600' to surface w/55 sxs CI-B cement. Cut off wellhead, install marker.

RDMOSU 3/12/97

RECEIVED
JUN 16 1997

OIL CON. DIV.
DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Pat Archuleta

TITLE

Staff Assistant

DATE

06-13-1997

TYPE OR PRINT NAME

Pat Archuleta

TELEPHONE NO.

303-830-5217

(This space for State

APPROVED BY

James C. ...

TITLE

Deputy O&G Inspector

DATE

6-18-97

CONDITIONS OF APPROVAL, IF ANY: