

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Basin Dakota Formation Dakota County San Juan
Initial XX Annual _____ Special _____ Date of Test 1-12-65
Company Southern Union Production Co. Lease Albright Well No. 7
Unit L Sec. 22 Twp. 29-N Rge. 10-W Purchaser El Paso Natural Gas Company
Casing 4-1/2" Wt. 10.5 I.D. 4.052 Set at 6620 Perf. 6312 To 6494
Tubing 1-1/2 Wt. 2.90 I.D. 1.610 Set at 6416 Perf. 6406 To 6416
Gas Pay: From 6312 To 6494 L 6406 xG .670 -GL 4292 Bar.Press. 12.0
Producing Thru: Casing _____ Tubing XX Type Well Single-Gas
Single-Bradenhead-G. G. or G.O. Dual
Date of Completion: 1-1-65 Packer _____ Reservoir Temp. _____

OBSERVED DATA

Tested Through (Recess) (Choke) (Recess)

Type Taps _____

Flow Data						Tubing Data		Casing Data		Duration of Flow Hr.
No.	(Prover) (Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h _w	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI						2042		2051		11 days
1.	2"	3/4	332		73	332	73	1131		3 hrs.
2.										
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_{wPf}}$	Pressure psia	Flow Temp. Factor F _t	Gravity Factor F _g	Compress. Factor F _{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.	12.3650		344	.9877	.9463	1.034	4111
2.							
3.							
4.							
5.							

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio _____ cf/bbl.
Gravity of Liquid Hydrocarbons _____ deg.
F_c _____ (1-e^{-S})

Specific Gravity Separator Gas _____
Specific Gravity Flowing Fluid _____
P_c 2063 P_c 4255969

No.	P _w P _t (psia)	P _t ²	F _c Q	(F _c Q) ²	(F _c Q) ² (1-e ^{-S})	P _w ²	P _c ² -P _w ²	Cal. P _w	P _w P _c
1.						1306449	2949520		554
2.									
3.									
4.									
5.									

Absolute Potential: 5413 MCFPD; n .75COMPANY Southern Union Production CompanyADDRESS P. O. Box 808 - Farmington, New MexicoAGENT and TITLE Verne Rockhold - Jr. EngineerWITNESSED Herman McNallyCOMPANY El Paso Natural Gas CompanyOriginal Signed By
VERNE ROCKHOLD(3) New Mexico O.C.C.

REMARKS

(1) Mr. Paul J. Clote(1) El Paso Natural Gas Co., Proration Dept., P.O. Box 1492, El Paso, Texas(1) Mr. H. L. Kindricks, Box 990, Farmington, New Mexico(1) Pan American Petroleum(1) File

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia
- P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- P_f = Meter pressure, psia.
- h_w = Differential meter pressure, inches water.
- F_g = Gravity correction factor.
- F_t = Flowing temperature correction factor.
- F_{pv} = Supercompressability factor.
- n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .